

INDUSTRIAL COMPONENT DATA

SAC-5P-MS/ 2,0-170/FS SCO VL 1549405 PHOENIX CONTACT

Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-MS/ 2,0-170/FS SCO VL



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-MS/ 2,0-170/FS SCO VL
Catalog number	1549405
Category	Sensor-actuator patch cord
Minimum order	100 Pcs
Document ID	EO-980454F280
Generated	2026-08-03

Product Overview

Sensor/actuator cable

Sensor/actuator cable, halogen-free PUR, grayish black RAL 7021, M12 SPEEDCON straight male connector, coding: A, to M12 SPEEDCON straight connection female, coding: A, cable length: 2 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Field Connectivity (IFC)**

Additional Product Information

Key Commercial Data

Orderkey 1549405

Packing unit 25 pc

Minimum order quantity 100 pc

Note Made to Order (non-returnable)

GTIN 4046356144926

Weight per Piece (excluding packing) 97.980 g

Custom tariff number 85444290

Country of origin PL (Poland)

Dimensions

Length of cable 2 m

General

Rated voltage 48 V AC

60 V DC

Cable

Cable type PUR, black, 5th conductor gray

Cable type (abbreviation) 115

Cable abbreviation Li9Y11Y-HF

UL AWM style 20549 / 10493 (80°C/300 V)

Conductor cross section 5x 0.34 mm²

AWG signal line 22

Conductor structure signal line 42x 0.10 mm

Core diameter including insulation 1.27 mm ±0.02 mm

Thickness, insulation ≥ 0.21 mm

Wire colors Brown, white, blue, black, gray

Overall twist 5 cores, twisted

External sheath, color black-gray RAL 7021

Outer sheath thickness approx. 0.7 mm

External cable diameter D 5 mm ±0.15 mm

Minimum bending radius, fixed installation 5 x D

Minimum bending radius, flexible installation 10 x D

Number of bending cycles 4000000

Bending radius 50 mm

Traversing path 10 m

Traversing rate 3 m/s

Acceleration 10 m/s²

Cable weight 35 kg/km

Outer sheath, material PUR

Material, filler PP

Material conductor insulation PP

Conductor material Bare Cu litz wires

Conductor resistance ≤ 58 Ω/km

Nominal voltage, cable ≤ 300 V

Test voltage, cable ≥ 3000 V

Special properties Flexible cable conduit capable

Silicone-free

Free of substances which would hinder coating with paint or varnish
flexible

Flame resistance in accordance with DIN UL-Style 20549
in accord...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-MS/ 2,0-170/FS SCO VL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.