

INDUSTRIAL COMPONENT DATA

SAC-5P-MS/ 2,7-115 BK SCO 1445761 PHOENIX CONTACT

Cable for sensors/actuators, 5-pole, PUR, black-gray RAL 7..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-MS/ 2,7-115 BK SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-MS/ 2,7-115 BK SCO
Catalog number	1445761
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-D291044DB7
Generated	2026-08-05

Product Overview

Cable for sensors/actuators, 5-pole, PUR, black-gray RAL 7021, Plug straight M12 SPEEDCON, coded, to the end of free cable, cable length: 2.7 m

Sensor/actuator cable, 5-pole, halogen-free PUR, greyish black RAL 7021, M12 SPEEDCON straight male connector, coding: A, to free cable end, cable length: 2.7 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Cable, sensor/actuator, 5-pin, PUR halogen free, black-gray RAL 7021, Plug straight M12 SPEEDCON, coding, to the free end of the conductor-length of cable: 2.7 m

Business

The code of the application One million four hundred forty five thousand seven hundred sixty one

The amount of the package (C#) 1 Unit

The minimum quantity of the order 50 Pcs

Note The production is linked to the application (no removal)

GTIN Four trillion forty six billion three hundred fifty six million six hundred six thousand six hundred twenty two

Weight per piece (excluding packing) 103,300 GRM

The number of corporate and commercial Eighty five million four hundred forty four thousand two hundred ninety

The country-of-origin PL (Poland).

Measures

The length of the cable 2.7 m
The length of the insulation from the free end 50 mm
Environmental conditions
The degree of protection IP65
IP67
IP68
The general
Rated current at 40 °C Four
Rated voltage 48 V AC
60 V DC
The number of poles in the Five
The resistance of the insulation $\geq 10 \text{ M}\Omega$
Coding The standard
An indication of the state of Don't
Over voltage category II
The degree of impurity, Three
The Material
Class of flammability according to UL 94 Hemoglobin (HB)
The Material of the contact CuSn
Material on the surface of the contact Ni/Au
The Material supporting the contact TPU GF
The Material of the body of the cable TPU, hardly inflammable, self-extinguishing
The Material of the anti - Zinc die casting is under pressure, nickel-plated
The rules and the...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-MS/ 2,7-115 BK SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.