

INDUSTRIAL COMPONENT DATA

SAC-5P-MS/ 6,5-927/MS SCO JLG 1400976 PHOENIX CONTACT Bus system cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-MS/ 6,5-927/MS SCO JLG



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-MS/ 6,5-927/MS SCO JLG
Catalog number	1400976
Category	Sensor-actuator patch cord
Minimum order	25 Pcs
Document ID	EO-E016F8100A
Generated	2026-08-04

Product Overview

Bus system cable

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data

Orderkey 1400976

Packing unit 1

GTIN 4046356514668

Custom tariff number 85444290

Dimensions

Length of cable 6.5 m

Ambient conditions

Degree of protection IP65

IP67

IP68

General

Rated current at 40°C 4 A

Rated voltage 48 V AC

60 V DC

Number of positions 5
Insulation resistance $\geq 100 \text{ M}\Omega$
Coding A - standard
Signal type/category CANopen®
DeviceNet™
Status display No
Overvoltage category II
Degree of pollution 3
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Standards and Regulations
Flammability rating according to UL 94 HB
Cable
Cable type DeviceNet™
Cable type (abbreviation) 927
UL AWM style 2464 (80°C/300 V)
Conductor cross section 2x 0.34 mm² (Signal line)
2x 0.34 mm² (Power supply)
1x 0.38 mm² (Drain wire)
AWG signal line 22
AWG power supply 22
Conductor structure signal line 44x 0.10 mm
Conductor structure, voltage supply 44x 0.10 mm
Core diameter including insulation 2.55 mm (Signal line)
1.37 mm (Power supply)
Thickness, insulation $\geq 0.3 \text{ mm}$ (Wire insulation power supply)
Wire colors Red-black, blue-white
Twisted pairs 2 cores to the pair
Type of pair shielding Aluminum-lined polyester foil
Overall twist 2 pairs with filler elements, around a drain wire in the center to the core
Shielding Tinned copper braided shield
Optical shield co...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-MS/ 6,5-927/MS SCO JLG with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.