

INDUSTRIAL COMPONENT DATA

SAC-5P-MS/8-PUR/FS YE VA SH 1409353 PHOENIX CONTACT

Sensor/actuator cable SAC-5P-MS/8-PUR/FS YE VA SH 1409353

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-MS/8-PUR/FS YE VA SH



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-MS/8-PUR/FS YE VA SH
Catalog number	1409353
Category	Sensor-actuator patch cord
Minimum order	100 Pcs
Document ID	EO-95AB34DF84
Generated	2026-08-06

Product Overview

Sensor/actuator cable - SAC-5P-MS/8-PUR/FS YE VA SH - 1409353

Sensor/actuator cable, 5-pole, halogen-free PUR, greyish black RAL 7021, shielded, M12 straight male connector, encoding: A, to M12 straight connection female, encoding: A, cable length: 8 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Sensor/actuator cable, 5-position, PUR halogen-free, black-gray RAL 7021, shielded, Plug straight M12, A-coded, on Socket straight M12, A-coded, cable length: 8 m

Key Commercial Data

Orderkey 1409353

Packing unit 1

GTIN 4046356869294

Custom tariff number 85444290

Dimensions

Length of cable 8 m

Ambient conditions

Degree of protection IP65

IP67

General

Rated current at 40°C 4 A

Rated voltage 48 V AC

60 V DC

Number of positions 5

Insulation resistance $\geq 10\text{ M}\Omega$

Coding A - standard

Status display No

Overvoltage category II

Degree of pollution 3

Insertion/withdrawal cycles ≥ 100

Material

Flammability rating according to UL 94 HB

Contact material CuSn

Contact surface material Ni/Au

Contact carrier material TPU GF

Material of grip body TPU, hardly inflammable, self-extinguishing

Material, knurls Stainless steel

Sealing material NBR

Standards and Regulations

Flammability rating according to UL 94 HB

Cable

Cable type PUR halogen-free black

Cable type (abbreviation) PUR

Cable abbreviation LiF9YC11Y

UL AWM style 20549

Conductor cross section $5 \times 0.34\text{ mm}^2$ (Signal line)

AWG signal line 22

Conductor structure signal line $42 \times 0.10\text{ mm}$

Core diameter including insulation $1.27\text{ mm} \pm 0.02\text{ mm}$ (Signal line)

Wire colors Brown, white, blue, black, gray

Overall twist 5 wires around filler to the core

Shielding Tinned copper braided shield

Optical shield covering 80 %

External sheath, color black-gray RAL 7021

External cable diameter $D\ 5.25\text{ mm} \pm 0.2\text{ mm}$

Smallest bending radius, fixed installation 26 mm

Smal...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-MS/8-PUR/FS YE VA SH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.