

INDUSTRIAL COMPONENT DATA

SAC-5P-MS/ 8,0-923/FS CAN SCO 1441470 PHOENIX CONTACT Bus system cable, CANopen®, 5-pole, halogen-free PUR, ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-MS/ 8,0-923/FS CAN SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-MS/ 8,0-923/FS CAN SCO
Catalog number	1441470
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-75E1B6828C
Generated	2026-08-04

Product Overview

Bus system cable, CANopen®, 5-pole, halogen-free PUR, silver grey RAL 7001, shielded, M12 straight connector, encoding: A, a M12 straight female, encoding: A, cable length: 8 m, Unshielded plug-in connector
Cable for sensors/actuators

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

ETIM for 1441470 Sensors (EC001855)
Feature Name
Feature Value
Number of poles (EF001391)
5
Type of electrical connection, field-sided (EF005525)
M12
Type of plug-in contact, field sided (EF006269)
Female (bus)
Positioning cable feed, field-sided (EF005928)
Straight

Type of electrical connection, box-sided (EF005524)
M12
Type of plug-in contact, box-sided (EF008386)
Male (plug)
Positioning cable feed, box-sided (EF005927)
Straight
Cable length (EF000536)
8 m
Material of cable sheath (EF004136)
Other
Halogen free (EF000025)
Yes
Colour cable sheath (EF008249)
Other
With LED indication (EF005950)
No
Screened (EF000881)
Yes
Vulcanize (EF004115)
No
Material contact body (EF008248)
Other
Material of contact surface (EF004020)
Other
Permitted cable outer temperature after assembling without vibration (EF001686)
-40 °C
Permitted cable outer temperature during assembling/handling (EF001685)
-20 °C
Rated current I_n (EF008250)
4 A
Rated voltage (EF000228)
48 V
Degree of protection (IP) (EF005474)
IP65

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-MS/ 8,0-923/FS CAN SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.