

INDUSTRIAL COMPONENT DATA

SAC-5P-MSB/0,25-PUR SH SCO 1544413 PHOENIX CONTACT

Sensor/actuator cable SAC-5P-MSB/0,25-PUR SH SCO 1544413

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-MSB/0,25-PUR SH SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-MSB/0,25-PUR SH SCO
Catalog number	1544413
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-A55308DC73
Generated	2026-08-06

Product Overview

Sensor/actuator cable - SAC-5P-MSB/0,25-PUR SH SCO - 1544413

Sensor/actuator cable, halogen-free PUR, greyish black RAL 7021, shielded, M12 SPEEDCON straight male connector, coding: B, to free cable end, cable length: 0.25 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Sensor/actuator cable, PUR halogen-free, black-gray RAL 7021, shielded, Plug straight M12 SPEEDCON, B-coded, on free cable end, cable length: 0.25 m

Key Commercial Data

Orderkey 1544413

Packing unit 1

GTIN 4046356115124

Custom tariff number 85444290

Dimensions

Length of cable 0.25 m

General

Rated voltage 48 V AC

60 V DC
Cable
Cable type PUR halogen-free black
Cable type (abbreviation) PUR
Cable abbreviation LiF9YC11Y
UL AWM style 20549
Conductor cross section 5x 0.34 mm² (Signal line)
AWG signal line 22
Conductor structure signal line 42x 0.10 mm
Core diameter including insulation 1.27 mm ±0.02 mm (Signal line)
Wire colors Brown, white, blue, black, gray
Overall twist 5 wires around filler to the core
Shielding Tinned copper braided shield
Optical shield covering 80 %
External sheath, color black-gray RAL 7021
External cable diameter D 5.25 mm ±0.2 mm
Smallest bending radius, fixed installation 26 mm
Smallest bending radius, movable installation 52 mm (up to +60°C)
Number of bending cycles 10000000
Bending radius 52 mm
Traversing path 10 m
Traversing rate 3 m/s
Acceleration 10 m/s²
Outer sheath, material PUR
Material conductor insulation PP
Conductor material Bare Cu litz wires
Insulation resistance 70 G?·km (at 20 °C)
Conductor resistance max. 57 ?/km (at 20 °C)
Nominal voltage, cable 300 V (at 20 °C)
Test voltage Core/Core 3000 V (at 20 °C)
Special properties Flexible cable conduit capable
Flame resistance in accordance with UL 758/1581 FT2
DIN EN 60332-2-2 (20 s)
Halogen-...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-MSB/0,25-PUR SH SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.