

INDUSTRIAL COMPONENT DATA

SAC-5P-P12MS/ 3,0-PUR/P12FS SH 1476910 PHOENIX CONTACT Sensor/actuator cable, 5-pole, halogen-free PUR, grey..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-P12MS/ 3,0-PUR/P12FS SH



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-P12MS/ 3,0-PUR/P12FS SH
Catalog number	1476910
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-61EFB9C04F
Generated	2026-08-05

Product Overview

Sensor/actuator cable, 5-pole, halogen-free PUR, greyish black RAL 7021, shielded (Advanced Shielding Technology), M12 Push-pull straight connector, coding: A, a M12 Push-pull straight female, coding: A, cable length: 3 m

Cable for sensors/actuators

Sensor/Actuator Cable, 5-Pole, Halogen-Free PUR, Greyish Black RAL 7021, Shielded (Advanced Shielding Technology), M12 Push-pull Straight Connector, Coding: A, Connected with Unconnected, A Straight Female M12 Push-pull, Coding: A, Cable Length: 3 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataassemblyConnection type Push-Pull

Item PropertiesProduct Type Sensor/Actuator Cables

Number of poles 5

application Standard

Number of Cable Outlets 1

Shielded Yes

Codification to

Insulation Properties

Surge Category II
Degree of pollution 3
Material Data Flammability class according to UL 94 V0
Outer Wrap, Material PUR
Conductive Material Naked Cu Conductor
Electrical Properties Contact resistance $\leq 5 \text{ m}\Omega$
Insulation resistance $\geq 100 \text{ M}\Omega$
Nominal voltage UN 48 V AC
60 V DC
Nominal Current IN 4 A
Protection Circuit Unplugged
Max. Conductor Resistance $58 \text{ m}\Omega/\text{km}$
Mechanical Properties Mechanical data
Plug Cycles ≥ 100
Max. bending cycles 1000000
Signage Status Indication No
Available Status Indication No
Connection data Connection technology
Connection type Push-Pull
Connecting Conductors
Connection type Push-Pull
Connectors Connection 1
Construction M12 Push-pull Straight Connector
Number of poles 5
Locking system Push-pull
Encoding Type to
Connection 2
Construction Straight Female M12 Push-pull
Number of poles 5
Locking system Push-pull
Encoding Type to
Cable/Line Cable length 3 m
Halogen-free PUR Black [PUR]
Dimension Scheme
Cable Weight 43 kg/km
UL AWM Style 20549 / 10493 (80°C/300V)
Number of poles 5
Shielded Yes
Cable type Halogen-free PUR Black [PUR]
Conductor Construction Signal Cable 42x 0.10 mm
AWG Signal Line 22
Line Section 5x 0.34 mm² (signal conductor)
Conductor diameter incl. insulation 1.27 mm $\pm 0.02 \text{ mm}$ (signal conductor)
Cable Outer Diameter 5.25 mm $\pm 0.2 \text{ mm}$
Out...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-P12MS/ 3,0-PUR/P12FS SH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.