

INDUSTRIAL COMPONENT DATA

SAC-5P-Y/2X1,5-PUR/A-1L-Z SCO 1425430 PHOENIX CONTACT Sensor/actuator cable SAC-5P-Y/2X1,5-PUR/A-1L-Z SCO 14..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-Y/2X1,5-PUR/A-1L-Z SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-Y/2X1,5-PUR/A-1L-Z SCO
Catalog number	1425430
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-1E332A02E5
Generated	2026-08-06

Product Overview

Sensor/actuator cable - SAC-5P-Y/2X1,5-PUR/A-1L-Z SCO - 1425430

Sensor/actuator cable, 3-pole halogen-free, M12 straight connector, coding: A SPEEDCON, a C valve connectors (8mm), with 1 LED, connected with Diode Z, cable length: 1.5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Field Connectivity (IFC)**

Additional Product Information

Sensor/actuator cable, 3-position, PUR halogen-free, black-gray RAL 7021, Plug straight M12 SPEEDCON, A-coded, on Valve connector C (8 mm), with 1 LED, connected with Z diode, cable length: 1.5 m

Key Commercial Data

Orderkey 1425430

Packing unit 1

GTIN 4055626399577

Custom tariff number 85444290

Dimensions

Length of cable 1.5 m

General

Rated voltage 24 V AC

24 V DC
Number of positions 3
Cable
Cable type PUR halogen-free black
Cable type (abbreviation) PUR
Cable abbreviation Li9Y11Y-HF
UL AWM style 20549
Conductor cross section 3x 0.5 mm²
AWG signal line 20
Conductor structure signal line 28x 0.15 mm
Core diameter including insulation 1.5 mm ±0.05 mm (Signal line)
Wire colors black 1, black 2, green/yellow
Overall twist 3 wires, twisted
External sheath, color black-gray RAL 7021
External cable diameter D 4.5 mm ±0.2 mm
Smallest bending radius, fixed installation 22.5 mm
Number of bending cycles 15000000
Bending radius 50 mm
Traversing path 0.9 m
Traversing rate 5 m/s
Acceleration 30 m/s²
Outer sheath, material PUR
Material conductor insulation PP
Conductor material Bare Cu litz wires
Insulation resistance min. 20 MΩ*km
Conductor resistance 39 Ω/km (at 20 °C)
Nominal voltage, cable ≤ 300 V
Test voltage, cable ≥ 1200 V
Flame resistance according to DIN VDE 0482
According to DIN EN 50265-2-1
Halogen-free in accordance with DIN VDE 0472 part 815
Other resistance largely oil-resistant
partly UV-resistant in accordance with DIN EN ISO 4892-2-A
Ambient temperature (operation) -40 °C...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-Y/2X1,5-PUR/A-1L-Z SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.