

INDUSTRIAL COMPONENT DATA

SAC-5PM12MS/0,64-92X/M12FSSHOD 1570226 PHOENIX CONTACT Bus System Cable, CANopen, DeviceNet, 5-Pole, Shielded..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5PM12MS/0,64-92X/M12FSSHOD



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5PM12MS/0,64-92X/M12FSSHOD
Catalog number	1570226
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-0AAA81ADAA
Generated	2026-08-01

Product Overview

Bus System Cable, CANopen, DeviceNet, 5-Pole, Shielded, M12 Straight Connector, Encoding: A, to M12 Straight Female, Coding: A, Cable Length: 0.64 m, Outdoor Applications, with Stainless Steel Knurling
Bus system cable

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Field Connectivity (IFC)**

Additional Product Information

Technical dataItem PropertiesProduct Type Ready-made data cable

Sensor Type CANopen®

Number of poles 5

application Outdoor spaces

Number of Cable Outlets 1

Shielded Yes

Codification to

Insulation Properties

Degree of pollution 3

InterfacesBus system CANopen®/DeviceNet™

Signal Type/Category CANopen®

DeviceNet™

SignageStatus Indication No

Available Status Indication No

Electrical PropertiesContact resistance $\leq 5\text{ m}\Omega$

Insulation resistance $\geq 100\text{ M}\Omega$

Nominal voltage UN 48 V AC

60 V DC

Nominal Current IN 4 A

Protection Circuit Unplugged

Transmission Medium copper

Mechanical PropertiesMechanical data

Plug Cycles ≥ 100

Material DataFlammability class according to UL 94 V0

Gasket material FPM

Grip body material PP

Contact material CuSn

Material: Contact Surface Ni/AU

Contact Support Material PP

Screw connection material Stainless steel

ConnectorsConnection 1

Construction M12 Straight Connector

Number of poles 5

Encoding Type A (Standard)

Connection 2

Construction Straight Female M12

Number of poles 5

Encoding Type A (Standard)

Cable/LineCable length 0.64 m

CANopen®/DeviceNet™, Outdoor, FRNC, Black [92X]

Dimension Scheme

Shielded Yes

UL AWM Style 21281 (80°C/300V)

Cable Weight 70 kg/km

Cable type CANopen®/DeviceNet™, Outdoor, FRNC, Black

Abbreviation LI2XCHX02XS

Cable Type (abbreviation) 92X

Signal Type/Category CANopen®

DeviceNet™

Cable Structure 2xAWG24/19+2xAWG22/19

Cable Outer Diameter 6.9 mm $\pm 0.3\text{ mm}$

Outer Wrap, Material FRNC

Outer Wrap, Color black

Wall Thickness Outer Wrap 1.15 mm...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5PM12MS/0,64-92X/M12FSSHOD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.