

INDUSTRIAL COMPONENT DATA

SAC-5PY-0,15FR/2X1,15-920MS-FS 1425946 PHOENIX CONTACT Cable bus system SAC-5PY-0,15 FR/2X1,15-920MS-FS 1425..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5PY-0,15FR/2X1,15-920MS-FS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5PY-0,15FR/2X1,15-920MS-FS
Catalog number	1425946
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-8F8CEEBC54
Generated	2026-08-05

Product Overview

Cable bus system - SAC-5PY-0,15 FR/2X1,15-920MS-FS - 1425946

Bus System Cable, CANopen®, DeviceNet™, 5-pole, halogen-free PUR, violet RAL 4001, shielded, Angled female M12 SPEEDCON, coding: A, a Straight connection female M12 SPEEDCON, coding: A and Straight male connector M12 SPEEDCON, coding: A, cable length: 1.15 m, All pluggable connectors unshielded, The display is positioned above pin 1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Field Connectivity (IFC)**

Additional Product Information

Cable, system bus, CANopen®DeviceNet , DeviceNet™, 5-pole, PUR halogen-free, violet, RAL 4001, shielded, connection socket angled M12 SPEEDCON, coded, to the connection socket straight M12 SPEEDCON, coded and Plug straight M12 SPEEDCON, coded, cable length: 1.15 m, All the plug connectors without shield, The screen is placed on the pin 1

Data commercial

Key order One million four hundred twenty five thousand nine hundred forty six

Packing unit 1 pcs

Key selling BF1GAD -

EAN Four trillion fifty five billion six hundred twenty six million four hundred thirty three thousand two hundred two

Unit weight (excluding packaging) 216,700 g

Tariff number tariff Eighty five million four hundred forty four thousand two hundred ninety

Measures

Cable length 1.15 m

Environmental conditions

Room temperature (service) -25 °C ... 90 °C (male / female)

Overview

Current sizing at 40 °C 4 To

Tension sizing 48 V AC

60 V DC

Number of poles Five

Insulation resistance $\geq 100 \text{ M}\Omega$

Encoding A - standard

Signal type/category CANopen®

DeviceNet™

Status indication Not

Category surge II

Pollution degree Three

Material

Class of flammability according to UL 94 HB

Material contact CuSn

Material contact surface Ni/Au

Material support of contacts TPU GF

Material body grip TPU fire-retardant, self-extinguishing

Material knurled Brass, nickel-plated

Material of the board NBR

Standards and specifications

Class of flammability according to UL 94 HB

Cable

Type of cable CAN Bus/DeviceNet

Cable type (abbreviation) Nine h...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5PY-0,15FR/2X1,15-920MS-FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.