

INDUSTRIAL COMPONENT DATA

SAC-5PY-F/M-F VP 1403330 PHOENIX CONTACT Y distributor SAC-5PY-F/M-F VP 1403330

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5PY-F/M-F VP



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5PY-F/M-F VP
Catalog number	1403330
Category	Sensor actuator adapter
Minimum order	50 Pcs
Document ID	EO-5FA50CB1E2
Generated	2026-08-06

Product Overview

Y distributor - SAC-5PY-F/M-F VP - 1403330

Y-splitter, 5-pole, Straight female M12, coding: A SPEEDCON, a Straight female M12, coding: A SPEEDCON and Straight connector M12, coding: A SPEEDCON, Unshielded plug-in connector

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Y distributor, 5-position, Socket straight M12 SPEEDCON, A-coded, on Socket straight M12 SPEEDCON, A-coded and Plug straight M12 SPEEDCON, A-coded, Connector unshielded

Key Commercial Data

Orderkey 1403330

Packing unit 1

GTIN 4046356648417

Custom tariff number 85366990

Dimensions

Center distance 21 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 90 °C

Degree of protection IP65

IP67

General

Rated current at 40°C 4 A

Rated voltage 60 V

Number of positions 5

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding A - standard

Standards/regulations M12 connector IEC 61076-2-101

Status display No

Overvoltage category II

Degree of pollution 3

Insertion/withdrawal cycles ≥ 100

Torque 0.4 Nm (M12 connector)

Material

Flammability rating according to UL 94 HB

Contact material CuZn

Contact surface material Ni/Au

Contact carrier material TPU GF

Material of grip body TPU, hardly inflammable, self-extinguishing

Material, knurls Zinc die-cast, nickel-plated

Sealing material NBR

Cable

Standards/specifications M12 connector IEC 61076-2-101

Standards and Regulations

Standard designation M12 connector

Standards/regulations IEC 61076-2-101

Flammability rating according to UL 94 HB

Environmental Product Compliance

REACH SVHC

Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss

eCl@ss 4.0 27060306

eCl@ss 4.1 27060306

eCl@ss 5.0 27060300

eCl@ss 5.1 27061800

eCl@ss...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5PY-F/M-F VP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.