

INDUSTRIAL COMPONENT DATA

SAC-6P-10,0-PVC/M12FRM PE SH 1414929 PHOENIX CONTACT Power cable, 6-position, PVC, orange RAL 2003, shielded..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-6P-10,0-PVC/M12FRM PE SH



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-6P-10,0-PVC/M12FRM PE SH
Catalog number	1414929
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-D7B56C2BDF
Generated	2026-08-05

Product Overview

Power cable, 6-position, PVC, orange RAL 2003, shielded (Advanced Shielding Technology), Socket angled M12, M-coded, on free cable end, cable length: 10 m, For AC current up to 8 A/690 V

Power cable, 6-pole, shielded (Advanced Shielding Technology), free cable end, to Elbow Female M12, coding: M, cable length: 10 m, for AC up to 8 A/690 V

Power cable, 6-position, PVC, orange RAL 2003, shielded (Advanced Shielding Technology), free cable end, on Socket angled M12, coding: M, cable length: 10 m, for AC current up to 8 A/690 V

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Technical dataProduct propertiesProduct type Power cable

Application Power supply

Number of positions 6

No. of cable outlets 1

Shielded yes

Coding M

Data management status

Article revision 04

Insulation characteristics
Overvoltage category III
Degree of pollution 3
Material specifications Flammability rating according to UL 94 V0
Material of grip body PP
Contact material CuZn
Contact surface material Ni/Au
Contact carrier material PA
Material for screw connection Zinc die-cast, nickel-plated
Electrical properties Insulation resistance $\geq 100 \text{ M}\Omega$
Nominal voltage UN 690 V AC
Nominal current IN 8 A
Connector Connection 1
Type free cable end
Connection 2
Type Socket angled M12
Coding type M (Power)
Cable/line Cable length 10 m
PVC orange [PVC]
Dimensional drawing
Cable weight 192 kg/km
UL AWM Style 2570 / 10914 (80°C/1000 V)
Number of positions 6
Shielded yes
Cable type PVC orange [PVC]
Conductor cross section $6 \times 1.5 \text{ mm}^2$
Wire diameter incl. insulation $2.4 \text{ mm} \pm 0.05 \text{ mm}$
External cable diameter $10.40 \text{ mm} \pm 0.25 \text{ mm}$
Outer sheath, material PVC
External sheath, color orange RAL 2003
Conductor material Bare Cu litz wires
Material wire insulation PVC
Single wire, color black 1, black 2, black 3, black 4, black 5, green/yellow
Thickness, insulation $\geq 0.36 \text{ mm}$
Thickness, outer sheath approx. 0.76 mm
Max. conductor resistance $\leq 15 \text{ } \Omega/\text{m}$ (at 20 °C)
Insulation resistance $\geq 100 \text{ M}\Omega \cdot \text{km}$ (at 20 °C)
Nominal voltage, cable $\leq 1000 \text{ V AC}$
Test voltage $\geq 10000 \text{ V AC}$ (Spark test)
Minimum bending radius, fixed installa...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-6P-10,0-PVC/M12FRM PE SH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.