

INDUSTRIAL COMPONENT DATA

SAC-6P-M12MS/ 4,0-970/M12FS 1081178 PHOENIX CONTACT

Bus system cable SAC-6P-M12MS/ 4,0-970/M12FS 1081178

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-6P-M12MS/ 4,0-970/M12FS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-6P-M12MS/ 4,0-970/M12FS
Catalog number	1081178
Category	Patch cord copper (twisted pair)
Minimum order	50 Pcs
Document ID	EO-81235CB045
Generated	2026-08-06

Product Overview

Bus system cable - SAC-6P-M12MS/ 4,0-970/M12FS - 1081178

Bus System Cable, VARAN, 6-Pole, Shielded, M12 Straight Connector, A, to M12 Straight Female, A, A, Cable Length: 4 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Bus system cable, VARAN, 6-position, SANTOPRENE halogen-free/TPE halogen-free, black RAL 9005, shielded, Plug straight M12, A-coded, on Socket straight M12, A-coded, cable length: 4 m

Key Commercial Data

Orderkey 1081178

Packing unit 1

GTIN 4055626809113

Custom tariff number 85444290

Dimensions

Length of cable 4 m

Ambient conditions

Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)

General

Rated current at 40°C 2 A

Rated voltage 30 V AC

30 V DC
Number of positions 6
Insulation resistance $\geq 100 \text{ M}\Omega$
Coding A - standard
Signal type/category VARAN
Status display No
Overvoltage category II
Degree of pollution 3
Material
Flammability rating according to UL 94 HB
Contact material CuZn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Standards and Regulations
Flammability rating according to UL 94 HB
Cable
Cable type VARAN
Cable type (abbreviation) 970
Cable abbreviation Li9YD12Y
Cable structure 1x2xAWG22/19 + 1x4xAWG24/19
Conductor cross section 4x 0.25 mm² (Signal line)
2x 0.38 mm² (Power supply)
AWG signal line 24
AWG power supply 22
Conductor structure signal line 19x 0.13 mm
Conductor structure, voltage supply 19x 0.16 mm
Core diameter including insulation 1.35 mm (Signal line)
1.5 mm (Power supply)
Wire colors Brown, blue, white/orange, white/green, green, orange
Type of pair shielding Tinned copper braided shield, 95....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-6P-M12MS/ 4,0-970/M12FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.