

INDUSTRIAL COMPONENT DATA

SAC-6P-M12MSM/ 3,0-PUR PE 1414953 PHOENIX CONTACT

Power cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-6P-M12MSM/ 3,0-PUR PE



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-6P-M12MSM/ 3,0-PUR PE
Catalog number	1414953
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-4838B6D4DD
Generated	2026-08-02

Product Overview

Power cable

Power cable, 6-pole halogen-free, M12 straight connector, coding: M, to free cable end, cable length: 3 m, for alternating current up to 8 A/690 V

Power cable, 6-position, PUR halogen-free, black-gray RAL 7021, Plug straight M12, coding: M, on free cable end, cable length: 3 m, for AC current up to 8 A/690 V

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Power cable

Application Power supply

Number of positions 6

No. of cable outlets 1

Shielded no

Coding M

Data management status

Article revision 06

Insulation characteristics

Overvoltage category III

Degree of pollution 3

Material specifications Flammability rating according to UL 94 V0

Material of grip body PP

Contact material CuZn

Contact surface material Ni/Au

Contact carrier material PA

Material for screw connection Zinc die-cast, nickel-plated

Electrical properties Insulation resistance $\geq 100 \text{ M}\Omega$

Nominal voltage UN 690 V AC

Nominal current IN 8 A

Connector Connection 1

Type Plug straight M12

Coding type M (Power)

Connection 2

Type free cable end

Cable/line Cable length 3 m

PUR halogen-free black [PUR]

Dimensional drawing

Cable weight 130 kg/km

Number of positions 6

Shielded no

Cable type PUR halogen-free black [PUR]

Conductor cross section $6 \times 1.5 \text{ mm}^2$

Wire diameter incl. insulation $2.35 \text{ mm} \pm 0.1 \text{ mm}$

External cable diameter $8.80 \text{ mm} \pm 0.25 \text{ mm}$

Outer sheath, material PUR

External sheath, color black-gray RAL 7021

Conductor material Bare Cu litz wires

Material wire insulation PP

Single wire, color black 1, black 2, black 3, black 4, black 5, green/yellow

Thickness, insulation $\geq 0.36 \text{ mm}$

Thickness, outer sheath approx. 0.90 mm

Max. conductor resistance $\leq 14.1 \text{ } \Omega/\text{km}$ (at $20 \text{ }^\circ\text{C}$)

Insulation resistance $\geq 1 \text{ G}\Omega\cdot\text{km}$ (at $20 \text{ }^\circ\text{C}$)

Nominal voltage, cable $\leq 1000 \text{ V AC}$

Test voltage $\geq 3000 \text{ V AC}$ (Spark test)

Minimum bending radius, fixed installation $5 \times D$

Minimu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-6P-M12MSM/ 3,0-PUR PE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.