

INDUSTRIAL COMPONENT DATA

SAC-6P-M8MS/3-PUR/8PM8FSSH OBS 1426185 PHOENIX

CONTACT Sensor/actuator cable

SAC-6P-M8MS/3-PUR/8PM8FSSH OBS ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-6P-M8MS/3-PUR/8PM8FSSH OBS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-6P-M8MS/3-PUR/8PM8FSSH OBS
Catalog number	1426185
Category	Sensor-actuator patch cord
Minimum order	100 Pcs
Document ID	EO-4FA098C4F2
Generated	2026-08-04

Product Overview

Sensor/actuator cable - SAC-6P-M8MS/3-PUR/8PM8FSSH OBS - 1426185

Sensor/actuator cable, 6-pole, halogen-free PUR, greyish black RAL 7021, shielded, M8 straight connector, encoding: A, to M8 straight female, cable length: 3 m, without PATG, Special connection, customer variant

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Sensor/actuator cable, 6-position, PUR halogen-free, black-gray RAL 7021, shielded, Plug straight M8, on Socket straight M8, cable length: 3 m, Without PATGs, Special wiring, customer version

Key Commercial Data

Orderkey 1426185

Packing unit 1

GTIN 4055626449135

Custom tariff number 85444290

Dimensions

Length of cable 3 m

Stripping length of the free conductor end 50 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)

General

Rated current at 40°C 1.5 A

Rated voltage 30 V AC

30 V DC

Number of positions 6

Coding A - standard

Standards/regulations M8 connector IEC 61076-2-104

Status display No

Protective circuit/component unwired

Overvoltage category II

Degree of pollution 3

Material

Flammability rating according to UL 94 HB

Contact material CuZn

Contact surface material Ni/Au

Contact carrier material TPU GF

Material of grip body TPU, hardly inflammable, self-extinguishing

Material, knurls Zinc die-cast, nickel-plated

Sealing material NBR

Standards and Regulations

Standard designation M8 connector

Standards/regulations IEC 61076-2-104

Flammability rating according to UL 94 HB

Cable

Cable type PUR halogen-free black

Cable type (abbreviation) PUR

Conductor cross section 6x 0.14 mm² (Signal line)

AWG signal line 26

Conductor structure signal line 18x 0.10 mm

Core diameter including insulation 1.05 mm ±0.02 mm

Wire colors Brown, white, black, blue, gray, pink

External sheath, color black-gray RAL 7021

External cable diameter 5.20 mm

Smallest bend...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-6P-M8MS/3-PUR/8PM8FSSH OBS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.