

INDUSTRIAL COMPONENT DATA

SAC-6P-MS/ 6,0-970/FS SCO 1421791 PHOENIX CONTACT

Bus system cable SAC-6P-MS/ 6,0-970/FS SCO 1421791

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-6P-MS/ 6,0-970/FS SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-6P-MS/ 6,0-970/FS SCO
Catalog number	1421791
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-C3F73ADD3A
Generated	2026-08-04

Product Overview

Bus system cable - SAC-6P-MS/ 6,0-970/FS SCO - 1421791

Bus system cable, VARAN (100 MBit/s), 6-pole, SANTOPRENE halogen-free/halogen-free TPE, black RAL 9005, shielded, M12 SPEEDCON straight connector, coding: A, a M12 SPEEDCON straight female, coding: A, cable length: 6 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Bus system cable, VARAN (100 Mbps), 6-position, SANTOPRENE halogen-free/TPE halogen-free, black RAL 9005, shielded, cable length: 6 m

Key Commercial Data

Orderkey 1421791

Packing unit 1

GTIN 4055626282275

Custom tariff number 85444290

Dimensions

Length of cable 6 m

General

Rated current at 40°C 2 A

Rated voltage 30 V AC

30 V DC

Number of positions 6
Coding A - standard
Signal type/category VARAN, 100 Mbps
Status display No
Overvoltage category II
Degree of pollution 3
Material
Flammability rating according to UL 94 HB
Contact material CuZn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Standards and Regulations
Flammability rating according to UL 94 HB
Cable
Cable type VARAN
Cable type (abbreviation) 970
Cable abbreviation Li9YD12Y
Cable structure 1x2xAWG22/19 + 1x4xAWG24/19
Conductor cross section 4x 0.25 mm² (Signal line)
2x 0.38 mm² (Power supply)
AWG signal line 24
AWG power supply 22
Conductor structure signal line 19x 0.13 mm
Conductor structure, voltage supply 19x 0.16 mm
Core diameter including insulation 1.35 mm (Signal line)
1.5 mm (Power supply)
Wire colors Brown, blue, white/orange, white/green, green, orange
Type of pair shielding Tinned copper braided shield, 95 % covering
Overall twist 1 star quad and 2 wires with 2 fillers
Shielding Tinned copper-braided shield, approx. 85% covering
External sheath, color black R...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-6P-MS/ 6,0-970/FS SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.