

INDUSTRIAL COMPONENT DATA

SAC-8P- 10,0-PUR/M 8FS VA 1412462 PHOENIX CONTACT

Sensor/actuator cable SAC-8P- 10,0-PUR/M 8FS VA 1412462

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-8P-10,0-PUR/M 8FS VA



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-8P-10,0-PUR/M 8FS VA
Catalog number	1412462
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-8D1E171406
Generated	2026-08-05

Product Overview

Sensor/actuator cable - SAC-8P- 10,0-PUR/M 8FS VA - 1412462

Sensor/actuator cable, 8-pole, halogen-free PUR, greyish black RAL 7021, free cable end, to Straight connection female M8, cable length: 10 m

Sensor/actuator cable, 8-position, PUR halogen-free, black-gray RAL 7021, free cable end, on Socket straight M8, coding: A, cable length: 10 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable

Application Standard

Number of positions 8

No. of cable outlets 1

Shielded no

Coding A

Insulation characteristics

Degree of pollution 3

Material specificationsFlammability rating according to UL 94 HB

Material of grip body TPU, hardly inflammable, self-extinguishing

Contact material CuSn

Contact surface material Ni/Au
Contact carrier material TPU GF
Material for screw connection Stainless steel
Electrical propertiesInsulation resistance $\geq 100 \text{ M}\Omega$
Nominal voltage UN 30 V AC
30 V DC
Nominal current IN 1.5 A
Mechanical propertiesMechanical data
Insertion/withdrawal cycles ≥ 100
SignalingStatus display no
Status display present No
Connection dataConductor connection
Tightening torque 0.2 Nm (M8 connectors)
ConnectorConnection 1
Type free cable end
Connection 2
Type Socket straight M8
Number of positions 8
Coding type A
Cable/lineCable length 10 m
PUR halogen-free black [PUR]
Dimensional drawing
Cable weight 31.4 kg/km
UL AWM Style 20549
Number of positions 8
Shielded no
Cable type PUR halogen-free black [PUR]
Conductor structure signal line 18x 0.10 mm
AWG signal line 26
Conductor cross section 8x 0.14 mm² (Signal line)
Wire diameter incl. insulation 1 mm $\pm 0.02 \text{ mm}$ (Signal line)
External cable diameter 5.10 mm $\pm 0.15 \text{ mm}$
Outer sheath, material PUR
External sheath, color black-gray RAL 7021
Conductor material Bare Cu litz wires
Material, filler PE
Material wire insulation PP
Single wire, color white, brown, green, yel...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-8P-10,0-PUR/M 8FS VA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.