

INDUSTRIAL COMPONENT DATA

SAC-8P-1,5-PUR/M8FS 0,25 1070721 PHOENIX CONTACT

Sensor/actuator cable SAC-8P-1,5-PUR/M8FS 0,25 1070721

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-8P-1,5-PUR/M8FS 0,25



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-8P-1,5-PUR/M8FS 0,25
Catalog number	1070721
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-624D8E640E
Generated	2026-08-06

Product Overview

Sensor/actuator cable - SAC-8P-1,5-PUR/M8FS 0,25 - 1070721

Sensor/actuator cable, 8-pole, halogen-free PUR, grayish black RAL 7021, free cable end, to Straight Connect Female M8,
Cable length: 1.5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Sensor/actuator cable, 8-position, PUR halogen-free, black-gray RAL 7021, free cable end, on Socket straight M8, cable
length: 1.5 m

Key Commercial Data

Orderkey 1070721

Packing unit 1

GTIN 4055626751344

Custom tariff number 85444290

Dimensions

Length of cable 1.5 m

Stripping length of the free conductor end 50 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)

General

Rated current at 40°C 1.5 A
Rated voltage 30 V AC
30 V DC
Number of positions 8
Coding A - standard
Standards/regulations M8 connector IEC 61076-2-104
Status display No
Protective circuit/component unwired
Degree of pollution 3
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Standards and Regulations
Standard designation M8 connector
Standards/regulations IEC 61076-2-104
Flammability rating according to UL 94 HB
Cable
Cable type PUR halogen-free black
Cable type (abbreviation) PUR
Cable abbreviation Li9Y11Y
UL AWM style 20549 / 10493 (80°C/300 V)
Conductor cross section 8x 0.25 mm²
AWG signal line 24
Conductor structure signal line 32x 0.10 mm
Core diameter including insulation 1.17 mm ±0.02 mm
Thickness, insulation >= 0.21 mm
Wire colors white, brown, green, yellow, gray, pink, blue, red
Overall twist 8 wires around filler to the core
External sheath, color black-gray RAL 7021
O...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-8P-1,5-PUR/M8FS 0,25 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.