

INDUSTRIAL COMPONENT DATA

SAC-8P-15,0-PVC/FR SCO 1410787 PHOENIX CONTACT

Sensor/actuator cable SAC-8P-15,0-PVC/FR SCO 1410787

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-8P-15,0-PVC/FR SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-8P-15,0-PVC/FR SCO
Catalog number	1410787
Category	Sensor-actuator patch cord
Minimum order	25 Pcs
Document ID	EO-44455EE2D3
Generated	2026-08-06

Product Overview

Sensor/actuator cable - SAC-8P-15,0-PVC/FR SCO - 1410787
 Sensor/actuator cable, PVC, black RAL 9005, cable length: 15 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Field Connectivity (IFC)**

Additional Product Information

Sensor/actuator cable, PVC, black RAL 9005
 Key Commercial Data
 Orderkey 1410787
 Packing unit 1
 GTIN 4046356915335
 Custom tariff number 85444290
 General
 Rated voltage 30 V AC
 30 V DC
 Cable
 Cable type PVC black
 Cable type (abbreviation) PVC
 Cable abbreviation LiYY
 UL AWM style 2464 / 1729 (80°C/300 V)

Conductor cross section 8x 0.25 mm² (Signal line)
AWG signal line 24
Conductor structure signal line 14x 0.15 mm
Core diameter including insulation 1.17 mm ±0.05 mm
Thickness, insulation ≥ 0.23 mm
Wire colors white, brown, green, yellow, gray, pink, blue, red
Overall twist 8 wires around filler to the core
External sheath, color black RAL 9005
Outer sheath thickness ≥ 0.76 mm
External cable diameter D 5.9 mm ±0.2 mm
Minimum bending radius, fixed installation 5 x D
Minimum bending radius, flexible installation 10 x D
Cable weight 54 kg/km
Outer sheath, material PVC
Material conductor insulation PVC
Conductor material Bare Cu litz wires
Insulation resistance ≥ 200 M^Ω·km (at 20 °C)
Conductor resistance 79 ^Ω/km (at 20 °C)
Nominal voltage, cable ≤ 300 V AC
Test voltage, cable ≥ 3000 V AC
Ambient temperature (operation) -40 °C ... 80 °C (cable, fixed installation)
-25 °C ... 80 °C (cable, flexible installation)
Environmental Product Compliance
REACH SVHC
Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"
Classifications
eCl@ss
eCl@ss 5.1 27061801
eCl@ss 6.0 27279200
eCl@s...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-8P-15,0-PVC/FR SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.