

INDUSTRIAL COMPONENT DATA

SAC-8P-30,0-540/M12FS YE VA 1414255 PHOENIX CONTACT

Sensor/actuator cable SAC-8P-30,0-540/M12FS YE VA 1414255

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-8P-30,0-540/M12FS YE VA



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-8P-30,0-540/M12FS YE VA
Catalog number	1414255
Category	Sensor-actuator patch cord
Minimum order	25 Pcs
Document ID	EO-D9C5C517FB
Generated	2026-08-06

Product Overview

Sensor/actuator cable - SAC-8P-30,0-540/M12FS YE VA - 1414255

Sensor/Actuator Cable, 8-pole, PVC, yellow, free cable end, to Straight Connecting Female M12, coding: A, cable length: 30 m

Sensor/actuator cable, 8-position, PVC, yellow, free cable end, on Socket straight M12, coding: A, cable length: 30 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable

Number of positions 8

No. of cable outlets 1

Shielded no

Coding A

Insulation characteristics

Overvoltage category II

Degree of pollution 3

Material specificationsFlammability rating according to UL 94 HB

Seal material NBR

Material of grip body TPU, hardly inflammable, self-extinguishing

Contact material CuZn

Contact surface material Ni/Au
Contact carrier material TPU GF
Material for screw connection Stainless steel
Electrical propertiesInsulation resistance $\geq 100 \text{ M}\Omega$
Nominal voltage UN 30 V AC
30 V DC
Nominal current IN 2 A
Mechanical propertiesMechanical data
Insertion/withdrawal cycles ≥ 100
SignalingStatus display no
Status display present No
ConnectorConnection 1
Type free cable end
Connection 2
Type Socket straight M12
Number of positions 8
Coding type A
Cable/lineCable length 30 m
PVC yellow [540]
Cable weight 54 kg/km
UL AWM Style 2464 (80°C/300 V)
Number of positions 8
Shielded no
Cable type PVC yellow [540]
Conductor structure signal line 32x 0.10 mm
AWG signal line 24
Conductor cross section 8x 0.25 mm²
Wire diameter incl. insulation 1.19 mm $\pm 0.02 \text{ mm}$
External cable diameter 5.90 mm $\pm 0.2 \text{ mm}$
Outer sheath, material PVC
External sheath, color yellow
Conductor material Bare Cu litz wires
Material wire insulation PVC
Single wire, color white, brown, green, yellow, gray, pink, blue, red
Thickness, insulation $\geq 0.23 \text{ mm}$
Thickness, outer sheath $\geq 0.76 \text{ mm}$
Overall twist 8 wires around filler to the core
Length o...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-8P-30,0-540/M12FS YE VA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.