

INDUSTRIAL COMPONENT DATA

SAC-8P-45,0-28X/M12FS OD 1417918 PHOENIX CONTACT

Sensor/actuator cable SAC-8P-45,0-28X/M12FS OD 1417918

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-8P-45,0-28X/M12FS OD



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-8P-45,0-28X/M12FS OD
Catalog number	1417918
Category	Sensor-actuator patch cord
Minimum order	25 Pcs
Document ID	EO-86FD969462
Generated	2026-08-05

Product Overview

Sensor/actuator cable - SAC-8P-45,0-28X/M12FS OD - 1417918

Cable for sensors/actuators

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Sensor/actuator cable, 8-position, PE-X halogen-free, black-gray RAL 7021, cable length: 45 m, for outdoor applications, with high-grade steel knurl

Key Commercial Data

Orderkey 1417918

Packing unit 1

GTIN 4055626128689

Custom tariff number 85444290

Dimensions

Length of cable 45 m

General

Rated current at 40°C 2 A

Rated voltage 30 V AC

30 V DC

Number of positions 8

Standards/regulations M12 connector IEC 61076-2-101

Status display No

Protective circuit/component unwired

Degree of pollution 3

Material

Flammability rating according to UL 94 V0

Standards and Regulations

Standard designation M12 connector

Standards/regulations IEC 61076-2-101

Flammability rating according to UL 94 V0

Cable

Cable type PE-X black

Cable type (abbreviation) 28X

Cable abbreviation Li2X2X

Conductor cross section 8x 0.25 mm²

AWG signal line 24

Conductor structure signal line 32x 0.10 mm

Core diameter including insulation 1.17 mm ±0.02 mm

Thickness, insulation approx. 0.25 mm (Core insulation)

Wire colors white, brown, green, yellow, gray, pink, blue, red

Overall twist 8 wires around filler to the core

Length of twist, overall twist 67 mm

External sheath, color black-gray RAL 7021

Outer sheath thickness approx. 1.3 mm

External cable diameter D 6.8 mm ±0.2 mm

Minimum bending radius, fixed installation 5 x D

Minimum bending radius, flexible installation 10 x D

Number of bending cycles 2000000

Minimum bending radius, drag chain applications 10 x D

Traversing path 10 m

Traversing rate 3 m/s

Acceleration 10....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-8P-45,0-28X/M12FS OD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.