

INDUSTRIAL COMPONENT DATA

SAC-8P- 5,0-500/M12FS VA 1571732 PHOENIX CONTACT

Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-8P-5,0-500/M12FS VA



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-8P-5,0-500/M12FS VA
Catalog number	1571732
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-4E5473E22E
Generated	2026-08-05

Product Overview

Sensor/actuator cable

Sensor/Actuator Cable, 8-Pole, PVC, Grey RAL 7001, Free Cable End, to Straight Connecting Female M12, Coding: A, Cable Length: 5 m, with Stainless Steel Knurling

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1571732

Packing unit 1 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4046356363839

Weight per Piece (excluding packing) 263.000 g

Custom tariff number 85444290

Country of origin PL (Poland)

Dimensions

Length of cable 5 m

Stripping length of the free conductor end 50 mm

Ambient conditions

Degree of protection IP65
IP67
IP68
General
Rated current at 40°C 2 A
Rated voltage 30 V AC
30 V DC
Number of positions 8
Insulation resistance $\geq 100 \text{ M}\Omega$
Coding A - standard
Status display No
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles ≥ 100
Material
Flammability rating according to UL 94 HB
Contact material CuZn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Stainless steel
Sealing material NBR
Standards and Regulations
Flammability rating according to UL 94 HB
Cable
Cable type PVC gray
Cable type (abbreviation) 500
UL AWM style 2464 / 1729 (80°C/300 V)
Conductor cross section $8 \times 0.25 \text{ mm}^2$
AWG signal line 24
Conductor structure signal line $32 \times 0.10 \text{ mm}$
Core diameter including insulation $1.19 \text{ mm} \pm 0.02 \text{ mm}$
Thickness, insulation $\geq 0.23 \text{ mm}$
Wire colors white, brown, green, yellow, gray, pink, blue, red
Overall twist 8 wires around filler to the core
External sheath, color gray RAL 7001
Outer sheath thickness $\geq 0.76 \text{ mm}$
External cable diameter $D 5.9 \text{ mm} \pm 0.2 \text{ mm}$
Minimum bending radius, fixed installation $5 \times D$
Minimum ben...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-8P-5,0-500/M12FS VA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.