

INDUSTRIAL COMPONENT DATA

SAC-8P-7,5-PUR/M12FS SH NC 1409382 PHOENIX CONTACT

Sensor/actuator cable SAC-8P-7,5-PUR/M12FS SH NC 1409382

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-8P-7,5-PUR/M12FS SH NC



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-8P-7,5-PUR/M12FS SH NC
Catalog number	1409382
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-0BB249ACA0
Generated	2026-08-06

Product Overview

Sensor/actuator cable - SAC-8P-7,5-PUR/M12FS SH NC - 1409382

Sensor/actuator cable, 8-pole, halogen-free PUR, greyish black RAL 7021, shielded, free cable end, to Straight connection female M12, coding: A, cable length: 7.5 m, The screen is not placed in the knurling

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Sensor/actuator cable, 8-position, PUR halogen-free, black-gray RAL 7021, shielded, free cable end, on Socket straight M12, A-coded, cable length: 7.5 m, Shield not connected to knurl

Key Commercial Data

Orderkey 1409382

Packing unit 1

GTIN 4046356869966

Custom tariff number 85444290

Dimensions

Length of cable 7.5 m

Stripping length of the free conductor end 50 mm

Ambient conditions

Degree of protection IP65

IP67

General

Rated current at 40°C 2 A

Rated voltage 30 V AC

30 V DC

Number of positions 8

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding A - standard

Status display No

Overvoltage category II

Degree of pollution 3

Insertion/withdrawal cycles ≥ 100 **Material**

Flammability rating according to UL 94 HB

Contact material CuZn

Contact surface material Ni/Au

Contact carrier material TPU GF

Material of grip body TPU, hardly inflammable, self-extinguishing

Material, knurls Zinc die-cast, nickel-plated

Sealing material NBR

Standards and Regulations

Flammability rating according to UL 94 HB

Cable

Cable type PUR halogen-free black

Cable type (abbreviation) PUR

Cable abbreviation LiF9YC11Y

UL AWM style 20549 / 10493 (80°C/300 V)

Conductor cross section $8 \times 0.25 \text{ mm}^2$ (Signal line)

AWG signal line 24

Conductor structure signal line $32 \times 0.10 \text{ mm}$ Core diameter including insulation $1.17 \text{ mm} \pm 0.02 \text{ mm}$

Thickness, insulation approx. 0.2 mm

Wire colors Brown, white, green, yellow, gray, pink, blue, red

Overall twist 8 wires around filler to the core

Shielding Tinned copper braided shield

Optical shield cove...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-8P-7,5-PUR/M12FS SH NC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.