

INDUSTRIAL COMPONENT DATA

SAC-8P-M12MS/0,15-PUR 1528383 PHOENIX CONTACT

Sensor/actuator cable, 8-pole, halogen-free PUR, greyish black..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-8P-M12MS/0,15-PUR



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-8P-M12MS/0,15-PUR
Catalog number	1528383
Category	Sensor-actuator patch cord
Minimum order	100 Pcs
Document ID	EO-456C1E7305
Generated	2026-08-03

Product Overview

Sensor/actuator cable, 8-pole, halogen-free PUR, greyish black RAL 7021, Straight M12 connector, coding: A, to free cable end, cable length: 0.15 m

Cable for sensors/actuators

Sensor/actuator cable, 8-position halogen-free, Plug straight M12, coding: A, connected with unwired, on free cable end, cable length: 0.15 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable

Number of positions 8

Application Standard

No. of cable outlets 1

Shielded no

Coding A

Insulation characteristics

Overvoltage category II

Degree of pollution 3

Material specifications Flammability rating according to UL 94 HB

Material of grip body TPU, hardly inflammable, self-extinguishing

Contact material CuZn

Contact surface material Ni/Au

Contact carrier material TPU GF

Material for screw connection Zinc die-cast, nickel-plated

Electrical properties Contact resistance $\leq 5 \text{ m}\Omega$

Insulation resistance $\geq 100 \text{ M}\Omega$

Nominal voltage UN 30 V AC

30 V DC

Nominal current IN 2 A

Protective circuit unwired

Mechanical properties Mechanical data

Insertion/withdrawal cycles ≥ 100

Signaling Status display No

Status display present No

Connector Connection 1

Type Plug straight M12

Number of positions 8

Coding type A

Connection 2

Type free cable end

Cable/line Cable length 0.15 m

PUR halogen-free black [PUR]

Dimensional drawing

Cable weight 46 kg/km

UL AWM Style 20549 / 10493 (80°C/300 V)

Number of positions 8

Shielded no

Cable type PUR halogen-free black [PUR]

Conductor structure signal line 32x 0.10 mm

AWG signal line 24

Conductor cross section 8x 0.25 mm² (Signal line)

Wire diameter incl. insulation 1.17 mm $\pm 0.02 \text{ mm}$

External cable diameter 5.9 mm $\pm 0.15 \text{ mm}$

Outer sheath, material PUR

External sheath, color black-gray RAL 7021

Conductor material Bare Cu litz wires

Material, filler PE

Material wire insulation PP

Single wire, color white...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-8P-M12MS/0,15-PUR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.