

INDUSTRIAL COMPONENT DATA

SAC-8P-M12MS/10-28X/M12FSSHOD 1408153 PHOENIX

CONTACT Sensor/actuator cable

SAC-8P-M12MS/10-28X/M12FSSHOD 14..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-8P-M12MS/10-28X/M12FSSHOD



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-8P-M12MS/10-28X/M12FSSHOD
Catalog number	1408153
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-9D65A16BC5
Generated	2026-08-06

Product Overview

Sensor/actuator cable - SAC-8P-M12MS/10-28X/M12FSSHOD - 1408153

Sensor/actuator cable, 8-pole, halogen-free PE-X/PE-X, grayish black RAL 7021, shielded, M12 straight male connector, coding: A, to M12 straight connection female, coding: A, cable length: 10 m, for outdoor applications, with stainless steel knurling

Sensor/actuator cable, 8-position, PE-X/PE-X halogen-free, black-gray RAL 7021, shielded, Plug straight M12, coding: A, on Socket straight M12, coding: A, cable length: 10 m, for outdoor applications, with high-grade steel knurl

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable

Application External areas

Number of positions 8

No. of cable outlets 1

Shielded yes

Coding A

Insulation characteristics

Degree of pollution 3

Material specificationsSeal material FPM
Material of grip body PP
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material PP
Material for screw connection Stainless steel
Electrical propertiesInsulation resistance $\geq 100 \text{ M}\Omega$
Nominal voltage UN 30 V AC
30 V DC
Nominal current IN 2 A
Mechanical propertiesMechanical data
Insertion/withdrawal cycles ≥ 100
SignalingStatus display no
Status display present No
Connection dataConductor connection
Tightening torque 0.4 Nm (M12 connector)
ConnectorConnection 1
Type Plug straight M12
Number of positions 8
Coding type A
Connection 2
Type Socket straight M12
Number of positions 8
Coding type A
Cable/lineCable length 10 m
PE-X black [28X]
Dimensional drawing
Cable weight 81 kg/km
Number of positions 8
Shielded yes
Cable type PE-X black [28X]
Conductor structure signal line 32x 0.10 mm
AWG signal line 24
Conductor cross section 8x 0.25 mm²
Wire diameter incl. insulation 1.17 mm $\pm 0.02 \text{ mm}$
External cable diameter 7.25 mm $\pm 0.3 \text{ mm}$
Outer sheath, material PE-X
External sheath, color black-gray RAL 7021
Conductor material Bare Cu litz wires
Material, filler PP yarn
Material wire insulation PE-X
Single wire, color white, brown, green, yellow, gray, pink, blue, red
Thickness, insulation approx. 0.25 mm (Core insulation)
Inn...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-8P-M12MS/10-28X/M12FSSHOD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.