

INDUSTRIAL COMPONENT DATA

SAC-8P-M12MS/60,0-PUR SH 1553407 PHOENIX CONTACT

Sensor/actuator cable, 8-pole, M12 straight connector, codi..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-8P-M12MS/60,0-PUR SH



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-8P-M12MS/60,0-PUR SH
Catalog number	1553407
Category	Sensor-actuator patch cord
Minimum order	5 Pcs
Document ID	EO-6DE8D0244C
Generated	2026-08-05

Product Overview

Sensor/actuator cable, 8-pole, M12 straight connector, coding: A, to free cable end, cable length: 60 m

Cable for sensors/actuators

Sensor/actuator cable, 8-position, Plug straight M12, coding: A, connected with unwired, on free cable end, cable length: 60 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable

Number of positions 8

Application Standard

No. of cable outlets 1

Shielded yes

Coding A

Insulation characteristics

Overvoltage category II

Degree of pollution 3

Material specificationsFlammability rating according to UL 94 HB

Material of grip body TPU, hardly inflammable, self-extinguishing

Contact material CuZn

Contact surface material Ni/Au
Contact carrier material TPU GF
Material for screw connection Zinc die-cast, nickel-plated
Electrical propertiesContact resistance $\leq 5 \text{ m}\Omega$
Insulation resistance $\geq 100 \text{ M}\Omega$
Nominal voltage UN 30 V AC
30 V DC
Nominal current IN 2 A
Protective circuit unwired
Mechanical propertiesMechanical data
Insertion/withdrawal cycles ≥ 100
SignalingStatus display No
Status display present No
ConnectorConnection 1
Type Plug straight M12
Number of positions 8
Coding type A
Connection 2
Type free cable end
Cable/lineCable length 60 m
PUR halogen-free black [PUR]
Dimensional drawing
Shielded yes
UL AWM Style 20549 / 10493 (80°C/300 V)
Cable weight 53 kg/km
Cable type PUR halogen-free black
Short symbol LiF9YC11Y
Cable type (abbreviation) PUR
External cable diameter 5.9 mm $\pm 0.2 \text{ mm}$
Outer sheath, material PUR
External sheath, color black-gray RAL 7021
Thickness, outer sheath approx. 0.5 mm
Conductor material Bare Cu litz wires
Conductor structure signal line 32x 0.10 mm
AWG signal line 24
Conductor cross section 8x 0.25 mm² (Signal line)
Material wire insulation PP
Thickness, insulation approx....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-8P-M12MS/60,0-PUR SH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.