


INDUSTRIAL COMPONENT DATA

SAC-8P-Y/2X 0,2-PUR/FS SCO DV 1569621 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-8P-Y/2X 0,2-PUR/FS SCO DV



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-8P-Y/2X 0,2-PUR/FS SCO DV
Catalog number	1569621
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-2A5DCBC0DF
Generated	2026-08-05

Product Overview

Sensor/actuator cable

Sensor/actuator cable, 8-pole, halogen-free PUR, greyish black RAL 7021, M12 SPEEDCON straight male connector, coding: A-coded, to M12 SPEEDCON straight connection female, coding: A-coded, cable length: 0.2 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data

Orderkey 1569621

Packing unit 1 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4046356336802

Weight per Piece (excluding packing) 41.000 g

Custom tariff number 85444290

Country of origin PL (Poland)

Dimensions

Length of cable 0.2 m

Ambient conditions

Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)

Degree of protection IP65

IP67

IP68

General

Rated current at 40°C 2 A

Rated voltage 30 V AC

30 V DC

Number of positions 8

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding A - standard

Status display No

Overvoltage category II

Degree of pollution 3

Material

Flammability rating according to UL 94 HB

Contact material CuZn

Contact surface material Ni/Au

Contact carrier material TPU GF

Material of grip body TPU, hardly inflammable, self-extinguishing

Material, knurls Zinc die-cast, nickel-plated

Sealing material NBR

Standards and Regulations

Flammability rating according to UL 94 HB

Cable

Cable type PUR halogen-free black

Cable type (abbreviation) PUR

Cable abbreviation Li9Y11Y-HF

Conductor cross section $4 \times 0.25 \text{ mm}^2$ (Signal line)

AWG signal line 24

Conductor structure signal line $32 \times 0.10 \text{ mm}$

Core diameter including insulation $1.17 \text{ mm} \pm 0.02 \text{ mm}$ (Signal line)

Thickness, insulation $\geq 0.21 \text{ mm}$ (Core insulation)

approx. 0.5 mm (Outer cable sheath)

Wire colors brown, white, blue, black

Overall twist 4 wires, twisted

External sheath, color black-gray RAL 7021

External cable diameter $D 3.95 \text{ mm} \pm 0.15 \text{ mm}$

Smallest bending radius, fixed installation...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-8P-Y/2X 0,2-PUR/FS SCO DV with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.