

INDUSTRIAL COMPONENT DATA

SAC-8PY-M/0,15-285/FR-F VP SCO 1403384 PHOENIX CONTACT Y-distributor, 8-pos., shielded, straight M12 SPEEDCO..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-8PY-M/0,15-285/FR-F VP SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-8PY-M/0,15-285/FR-F VP SCO
Catalog number	1403384
Category	Sensor actuator adapter
Minimum order	150 Pcs
Document ID	EO-30DDBED9D1
Generated	2026-08-04

Product Overview

Y-distributor, 8-pos., shielded, straight M12 SPEEDCON plug (A-coded) to angled M12 SPEEDCON socket (A-coded), with shielded PUR cable, length: 0.15 m, and straight M12 SPEEDCON socket (A-coded)

Y Splitter, 8 poles, pant., female connection. Rec. M12 SPEEDCON, codif. A, in female connection. acod. M12 SPEEDCON, codif. A, c. PUR duct pant., length: 0.15 m and rec male connector. M12 SPEEDCON, codif. To

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1403384
Packing unit 1
GTIN 4046356651462
Custom tariff number 85444290
Drawings
Ambient conditions
Material
Cable
Classifications

[Dimensions](#)

[General](#)

[Standards and Regulations](#)

[Environmental Product Compliance](#)

[Drawings](#)

[Circuit diagram](#)

[Contact assignment of the M12 Y distributor](#)

[Schematic diagram](#)

[Pin assignment M12 plug, 8-pos., A-coded, view plug side](#)

[Schematic diagram](#)

[Pin assignment M12 socket, 8-pos., A-coded, view female side](#)

[Cable cross section](#)

[PUR, gray, shielded \[285\]](#)

[Back to top](#)[Dimensions](#)

[Length of cable 0.15 m](#)

[Back to top](#)[Ambient conditions](#)

[Degree of protection IP65](#)

[IP67](#)

[Back to top](#)[General](#)

[Rated current at 40°C 2 A](#)

[Rated voltage 30 V AC](#)

[30 V DC](#)

[Number of positions 8](#)

[Insulation resistance \$\geq 100 \text{ M}\Omega\$](#)

[Coding A - standard](#)

[Standards/regulations M12 connector](#)

[Status display No](#)

[Overvoltage category II](#)

[Degree of pollution 3](#)

[Insertion/withdrawal cycles \$\geq 100\$](#)

[Back to top](#)[Material](#)

[Flammability rating according to UL 94 HB](#)

[Contact material CuZn](#)

[Contact surface material Ni/Au](#)

[Contact carrier material TPU GF](#)

[Material of grip body TPU, hardly inflammable, self-extinguishing](#)

[Material, knurls Zinc die-cast, nickel-plated](#)

[Sealing material NBR](#)

[Back to top](#)[Standards and Regulations](#)

[Standards/specifications M12 connector](#)

[Flammability rating according to UL 94 HB](#)

[Back to top](#)[Cable](#)

[Cable type PUR, gray, shielded](#)

[Cable type \(abbreviation\) 285](#)

[Cable abbreviation Li12YC11Y-HF](#)

[Conductor cross section 4x 2x 0.25 mm² \(Signal line\)](#)

[1x 0.25 mm² \(Drain wire\)](#)

AWG signal line 24...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-8PY-M/0,15-285/FR-F VP SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.