

INDUSTRIAL COMPONENT DATA

SAC-M12MR/1,5-PUR/2XA-1L-S/0,1 1572430 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-M12MR/1,5-PUR/2XA-1L-S/0,1



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-M12MR/1,5-PUR/2XA-1L-S/0,1
Catalog number	1572430
Category	Sensor-actuator patch cord
Minimum order	100 Pcs
Document ID	EO-9E6E21AC8E
Generated	2026-08-06

Product Overview

Sensor/actuator cable

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Field Connectivity (IFC)**

Additional Product Information

Key Commercial Data

Orderkey 1572430

Packing unit 1 pc

Minimum order quantity 100 pc

Note Made to Order (non-returnable)

GTIN 4046356409834

Weight per Piece (excluding packing) 170.000 g

Custom tariff number 85444290

Country of origin PL (Poland)

Dimensions

Length of cable 1.5 m

Ambient conditions

Degree of protection IP67

General

Rated current at 40°C 4 A

Rated voltage 24 V AC
24 V DC
Number of positions 3
Insulation resistance $\geq 100 \text{ M}\Omega$
Coding A - standard
Status display 1 LED
Protective circuit/component Z diode
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles ≥ 100
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Valve plug contact material CuSn
Valve plug contact surface material Ag
Valve plug contact insert material PBT
Material housing valve plug PBT
Sealing material TPU (Flat gasket valve plug)
Standards and Regulations
Flammability rating according to UL 94 HB
Environmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"
Classifications
eCl@ss 4.027060306eCl@ss 4.127060306eCl@ss 5.027061801eCl@ss 5.127061800eCl@ss 6.027279200eCl@ss
7.027279218eCl@ss 8.027279218eCl@ss 9.027060311
ETIM 3.0EC001855ETIM 4.0EC001855ETIM 5.0EC001855ETIM 6.0EC001855
UNSPSC 6.0131251501UNSPSC 7.0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-M12MR/1,5-PUR/2XA-1L-S/0,1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.