

INDUSTRIAL COMPONENT DATA

SACB-8/16-15,0PUR SH 1445729 PHOENIX CONTACT

Sensor/actuator box, without LED, with master cable, markers an..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACB-8/16-15,0PUR SH



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACB-8/16-15,0PUR SH
Catalog number	1445729
Category	Passive sensor-actuator interface (with cable)
Minimum order	10 Pcs
Document ID	EO-CAD14B377C
Generated	2026-08-02

Product Overview

Sensor/actuator box, without LED, with master cable, markers and double-occupied slots

Sensor/actuator box, without LED, with main cable, signage signs and double-supplied plug-in stations

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > QUICKON Installation System (QPD)

Additional Product Information

Key Commercial Data

Orderkey 1445729

Packing unit 1 pc

Minimum order quantity 10 pc

GTIN 4046356587792

Weight per Piece (excluding packing) 3,940.000 g

Custom tariff number 85444290

Country of origin PL (Poland)

Drawings

Ambient conditions

Insulation material

Standards and Regulations

Environmental Product Compliance**General****Master cable connection data****Pin assignment****Cable****Classifications****Drawings****Dimensional drawing****Circuit diagram****Schematic diagram****M12 slot, socket, 5-pos.****Cable cross section****PUR/PVC shielded, black [PUR]****Back to topGeneral****Rated voltage 48 V****60 V DC****Current carrying capacity per I/O signal 2 A****Current carrying capacity per slot 4 A****Total rated current 12 A****Number of positions 5****Number of slots 8****Flammability rating according to UL 94 V0****Sensor/actuator connection system M12 socket**

Note NOTE: Observe the permissible bending radii when laying conductors, since the degree of protection may be put in jeopardy if the bending forces are too high. Alleviate mechanical loads upstream of the connector, e.g. by using cable ties.

Unused slots are to be sealed off prior to commissioning. Suitable sealing elements are to be found under "Accessories".

Back to topAmbient conditions**Degree of protection IP65****IP67****Ambient temperature (operation) -25 °C ... 70 °C****-40 °C ... 90 °C (for fixed installation)****-5 °C ... 80 °C (for flexible installation)****Back to topMaster cable connection data****Connection method Fixed connection****Length of cable 15 m****Tightening torque slot sensor/...****REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send PHOENIX CONTACT / SACB-8/16-15,0PUR SH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.