

INDUSTRIAL COMPONENT DATA

SACB-8/16- 5,0PUR P12 SH 1155993 PHOENIX CONTACT

Distribution box, application: Standard, extended requireme..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACB-8/16-5,0PUR P12 SH



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACB-8/16-5,0PUR P12 SH
Catalog number	1155993
Category	Passive sensor-actuator interface (with cable)
Minimum order	1 Pcs
Document ID	EO-D1EE6B2384
Generated	2026-08-02

Product Overview

Distribution box, application: Standard, extended requirements, connection type: M12 Metal female connector / M12 Push-Pull female connector, number of plug-in stations: 8, number of poles: 5, coding: A, occupation of plug-in stations: Double, status indication: no, Universal; Main cable connection: Fixed connection 180°, PUR/PVC, cable length: 5 m, shielding: yes

Sensor/actuator box, application: Standard, connection type: Female connector M12 Metal, number of plug-in seats: 8, number of poles: 5, coding: A - standard, occupation of plug-in positions: Double, status indication: No, Universal; main cable connection: 180° fixed connection, PUR/PVC, cable length: 5 m, shielding: yes

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > QUICKON Installation System (QPD)**

Additional Product Information

ETIM for 1155993 Sensors (EC002585)

Feature Name

Feature Value

Length of the preassembled cable (EF007300)

5 m

Cable length configurable (EF007301)

No

Number of sensor-/actuator-slots (EF006939)

8

Number of channels per connector slot (EF006885)
2

Number of poles sensor/actuator slots (EF007402)
5

Rated voltage (EF000228)
48 V

Operating voltage (EF003983)
48 V

Max. current carrying capacity per socket (EF004038)
2 A

Max. total current (EF004039)
12 A

Material of contact surface (EF004020)
Gold

Material insulation body (EF007543)
Polyamide (PA)

With LED indication (EF005950)
No

With potential separation (EF003272)
No

Connection for NPN-sensors (EF006817)
Yes

Fix cable version suitable for cable guide chain (EF007461)
Yes

Housing colour (EF000136)
Silver

Operating temperature (EF002393)
-25 °C

Degree of protection (IP) (EF005474)
IP65

Explosion safety category for gas (EF003997)
Other

Explosion safety category for dust (EF003998)
Other

Width (EF000008)
58 mm

Height (EF000040)
26 mm

Depth (EF000049)
153 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACB-8/16-5,0PUR P12 SH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.