

INDUSTRIAL COMPONENT DATA

SACB-8/16-L-C QO 1156006 PHOENIX CONTACT Distribution box, connection type: QUICKON, 0.14 mm² ... 0.75 mm², ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACB-8/16-L-C QO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACB-8/16-L-C QO
Catalog number	1156006
Category	Passive sensor-actuator interface (without cable)
Minimum order	1 Pcs
Document ID	EO-2AA3CEC25E
Generated	2026-08-04

Product Overview

Distribution box, connection type: QUICKON, 0.14 mm² ... 0.75 mm², number of plug-in stations: 8, number of poles: 5, occupancy of plug-in stations: Double, status indication: yes, PNP; Main cable connection: 180° plug-in screw connection, shielding: no, In a 5-conductor connection, max. connection capacity of 0.5 mm²

Sensor/actuator box, connection type: QUICKON, 0.14 mm² ... 0.5 mm², number of plug-in seats: 8, number of poles: 5, occupation of plug-in seats: Double, status indication: Yes, pnp; main cable connection: Connection by 180° pluggable screw, shielding: no, Possibility of connection of 4 conductors with 0.75 mm²

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > QUICKON Installation System (QPD)

Additional Product Information

ETIM for 1156006 Sensors (EC003558)

Feature Name

Feature Value

Connectable conductor cross section (EF008200)

0.14 mm²

Cable outer diameter for cable gland (EF007302)

7 mm

Number of sensor-/actuator-slots (EF006939)

8

Number of channels per connector slot (EF006885)

2

Type of branches for sensor-/actuator cables (EF006972)

Insulation displacement connection

Number of poles sensor/actuator slots (EF007402)

5

Operating voltage (EF003983)

24 V

Max. current carrying capacity per I/O signal (EF004037)

10 A

Max. total current (EF004039)

10 A

Material of contact surface (EF004020)

Other

With LED indication (EF005950)

Yes

With potential separation (EF003272)

No

Connection for NPN-sensors (EF006817)

No

Operating temperature (EF002393)

-30 °C

Degree of protection (IP) (EF005474)

IP65

Explosion safety category for gas (EF003997)

Other

Explosion safety category for dust (EF003998)

Other

Width (EF000008)

58 mm

Height (EF000040)

45 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACB-8/16-L-C QO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.