

**INDUSTRIAL COMPONENT DATA**

# SACB- 8/3-L-30,0PUR-M8 HD 1197339 PHOENIX CONTACT

## Distribution box, application: Standard, connection type: ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACB-8/3-L-30,0PUR-M8 HD



|                 |                                                |
|-----------------|------------------------------------------------|
| Manufacturer    | PHOENIX CONTACT                                |
| MPN / Reference | SACB-8/3-L-30,0PUR-M8 HD                       |
| Catalog number  | 1197339                                        |
| Category        | Passive sensor-actuator interface (with cable) |
| Minimum order   | 1 Pcs                                          |
| Document ID     | EO-C63833A48C                                  |
| Generated       | 2026-08-05                                     |

### Product Overview

Distribution box, application: Standard, connection type: Female M8 Metal, number of plug-in stations: 8, number of poles: 3, coding: A, occupancy of plug-in stations: single, status indication: yes, PNP; Main cable connection: Fixed connection 180°, PUR/PVC, cable length: 30 m, shielding: no

Sensor/actuator box, application: Standard, connection type: Female M8 Metal, number of plug-in seats: 8, number of poles: 3, coding: A - standard, occupation of plug-in positions: simple, status indication: Yes, pnp; main cable connection: 180° fixed connection, PUR/PVC, cable length: 30 m, shielding: no

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; QUICKON Installation System (QPD)

### Additional Product Information

ETIM for 1197339 Sensors (EC002585)

Feature Name

Feature Value

Length of the preassembled cable (EF007300)

30 m

Cable length configurable (EF007301)

No

Number of sensor-/actuator-slots (EF006939)

8

Number of channels per connector slot (EF006885)

1  
Type of branches for sensor-/actuator cables (EF006972)  
M8  
Number of poles sensor/actuator slots (EF007402)  
3  
Rated voltage (EF000228)  
24 V  
Operating voltage (EF003983)  
24 V  
Max. current carrying capacity per socket (EF004038)  
2 A  
Max. total current (EF004039)  
6 A  
Material contact body (EF008248)  
Other copper alloys  
Material of contact surface (EF004020)  
Nickel  
Material insulation body (EF007543)  
Other  
With LED indication (EF005950)  
Yes  
With potential separation (EF003272)  
No  
Connection for NPN-sensors (EF006817)  
No  
Fix cable version suitable for cable guide chain (EF007461)  
No  
Housing colour (EF000136)  
Black  
Operating temperature (EF002393)  
-25 °C  
Degree of protection (IP) (EF005474)  
IP67  
Explosion safety category for gas (EF003997)  
Other  
Explosion safety category for dust (EF003998)  
Other  
Width (EF000008)  
30 mm  
Height (EF000040)  
20 mm  
Depth (EF000049)  
129.5 mm

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACB-8/3-L-30,0PUR-M8 HD with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.