

**INDUSTRIAL COMPONENT DATA**

# SACB- 8/3-L-C-M8 HD GG 1197612 PHOENIX CONTACT Base housing distribution box, application: Standard, connect..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACB-8/3-L-C-M8 HD GG



|                 |                                                   |
|-----------------|---------------------------------------------------|
| Manufacturer    | PHOENIX CONTACT                                   |
| MPN / Reference | SACB-8/3-L-C-M8 HD GG                             |
| Catalog number  | 1197612                                           |
| Category        | Passive sensor-actuator interface (without cable) |
| Minimum order   | 1 Pcs                                             |
| Document ID     | EO-436DAFA8C1                                     |
| Generated       | 2026-08-02                                        |

## Product Overview

Base housing distribution box, application: Standard, connection type: Female M8 Metal, number of plug-in stations: 8, number of poles: 3, coding: A, occupation of plug-in stations: single, status indication: yes, PNP; Main cable connection: Plug-in connection of main cable, shielding: No

Sensor/actuator box, base housing, application: Standard, connection type: Female M8 Metal, number of plug-in seats: 8, number of poles: 3, coding: A - standard, occupation of plug-in positions: simple, status indication: Yes, pnp; Main cable connection: Plug-in main cable connection, shielding: no

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; QUICKON Installation System (QPD)

## Additional Product Information

ETIM for 1197612 Sensors (EC003558)

Feature Name

Feature Value

Number of sensor-/actuator-slots (EF006939)

8

Number of channels per connector slot (EF006885)

1

Type of branches for sensor-/actuator cables (EF006972)

M8

Number of poles sensor/actuator slots (EF007402)

3

Operating voltage (EF003983)

24 V

Max. current carrying capacity per I/O signal (EF004037)

8 A

Max. total current (EF004039)

8 A

Material of contact surface (EF004020)

Other

With LED indication (EF005950)

Yes

With potential separation (EF003272)

No

Connection for NPN-sensors (EF006817)

No

Operating temperature (EF002393)

-25 °C

Degree of protection (IP) (EF005474)

IP67

Explosion safety category for gas (EF003997)

Other

Explosion safety category for dust (EF003998)

Other

Width (EF000008)

30 mm

Height (EF000040)

17 mm

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACB-8/3-L-C-M8 HD GG with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.