

INDUSTRIAL COMPONENT DATA

SACB- 8/4-L-10,0PUR-M8 HD 1197319 PHOENIX CONTACT

Distribution box, application: Standard, connection type: ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACB-8/4-L-10,0PUR-M8 HD



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACB-8/4-L-10,0PUR-M8 HD
Catalog number	1197319
Category	Passive sensor-actuator interface (with cable)
Minimum order	1 Pcs
Document ID	EO-6E5208D2A6
Generated	2026-08-02

Product Overview

Distribution box, application: Standard, connection type: Female M8 Metal, number of plug-in stations: 8, number of poles: 4, coding: A, occupation of plug-in stations: Double, status indication: Yes, PNP. Main cable connection: Fixed connection 180°, PUR/PVC, cable length: 10 m, shielding: no

Sensor/actuator box, application: Standard, connection type: Female M8 Metal, number of plug-in seats: 8, number of poles: 4, coding: A - standard, occupation of plug-in positions: Double, status indication: Yes, pnp; main cable connection: 180° fixed connection, PUR/PVC, cable length: 10 m, shielding: no

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > QUICKON Installation System (QPD)

Additional Product Information

ETIM for 1197319 Sensors (EC002585)

Feature Name

Feature Value

Length of the preassembled cable (EF007300)

10 m

Cable length configurable (EF007301)

No

Number of sensor-/actuator-slots (EF006939)

8

Number of channels per connector slot (EF006885)

2

Type of branches for sensor-/actuator cables (EF006972)

M8

Number of poles sensor/actuator slots (EF007402)

4

Rated voltage (EF000228)

24 V

Operating voltage (EF003983)

24 V

Max. current carrying capacity per socket (EF004038)

2 A

Max. total current (EF004039)

6 A

Material contact body (EF008248)

Other copper alloys

Material of contact surface (EF004020)

Nickel

Material insulation body (EF007543)

Other

With LED indication (EF005950)

Yes

With potential separation (EF003272)

No

Connection for NPN-sensors (EF006817)

No

Fix cable version suitable for cable guide chain (EF007461)

No

Housing colour (EF000136)

Black

Operating temperature (EF002393)

-25 °C

Degree of protection (IP) (EF005474)

IP67

Explosion safety category for gas (EF003997)

Other

Explosion safety category for dust (EF003998)

Other

Width (EF000008)

30 mm

Height (EF000040)

20 mm

Depth (EF000049)

129.5 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACB-8/4-L-10,0PUR-M8 HD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.