

## INDUSTRIAL COMPONENT DATA

# SACB-PT-H180-10/3-M8 HD 1197658 PHOENIX CONTACT

## Connection cover, application: Standard, connection type: Fe..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACB-PT-H180-10/3-M8 HD



|                 |                                                   |
|-----------------|---------------------------------------------------|
| Manufacturer    | PHOENIX CONTACT                                   |
| MPN / Reference | SACB-PT-H180-10/3-M8 HD                           |
| Catalog number  | 1197658                                           |
| Category        | Passive sensor-actuator interface (without cable) |
| Minimum order   | 1 Pcs                                             |
| Document ID     | EO-78D7C3896E                                     |
| Generated       | 2026-08-04                                        |

## Product Overview

Connection cover, application: Standard, connection type: Female M8 Metal, number of plug-in stations: 10, number of poles: 3, occupation of plug-in stations: single, status indication: No, Universal. Main cable connection: Push-in 180° plug-in spring connection, shielding: No

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                     |
|--------------|-----------------------------------------------------|
| Catalog path | PHOENIX CONTACT > QUICKON Installation System (QPD) |
|--------------|-----------------------------------------------------|

## Additional Product Information

ETIM for 1197658 Sensors (EC003558)

Feature Name

Feature Value

Connectable conductor cross section (EF008200)

0.2 mm<sup>2</sup>

Cable outer diameter for cable gland (EF007302)

6 mm

Number of sensor-/actuator-slots (EF006939)

10

Number of channels per connector slot (EF006885)

1

Type of branches for sensor-/actuator cables (EF006972)

M8

Number of poles sensor/actuator slots (EF007402)

3

Operating voltage (EF003983)

24 V

Max. current carrying capacity per I/O signal (EF004037)

8 A

Max. total current (EF004039)

8 A

With LED indication (EF005950)

No

With potential separation (EF003272)

No

Connection for NPN-sensors (EF006817)

Yes

Operating temperature (EF002393)

-25 °C

Degree of protection (IP) (EF005474)

IP67

Explosion safety category for gas (EF003997)

Other

Explosion safety category for dust (EF003998)

Other

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACB-PT-H180-10/3-M8 HD with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.