

INDUSTRIAL COMPONENT DATA

SACC-BP-F-M12/VAR-2,4/3,2-9TIP 1414233 PHOENIX CONTACT Housing screw connection

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-BP-F-M12/VAR-2,4/3,2-9TIP



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-BP-F-M12/VAR-2,4/3,2-9TIP
Catalog number	1414233
Category	Housing for circular connectors
Minimum order	10 Pcs
Document ID	EO-885F4FAB08
Generated	2026-08-05

Product Overview

Housing screw connection

M12 housing cable gland with tolerance compensation function, for THR-capable M12 straight female contact inserts. Suitable for 2.4mm faceplate wall thicknesses... 3.2 mm.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Field Device Connectors (FDC)**

Additional Product Information

Key Commercial Data

Orderkey 1414233

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

GTIN 4055626022741

Weight per Piece (excluding packing) 10.480 g

Custom tariff number 79070000

Country of origin DE (Germany)

Ambient conditions

Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)

-40 °C ... 85 °C (without mechanical actuation)

Degree of protection IP67 (correctly plugged in and locked)

General

Note The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of pollution, the connector must be sealed using a protective cap > IP54. The M12 housing screw connection can only be used in conjunction with mating connectors and protective caps with M12 standard thread. Mating connectors with SPEEDCON thread cannot be used.

Standards/regulations M12 connector IEC 61076-2-101

Insertion/withdrawal cycles > 100

Torque 0.6 Nm (Tightening torque of mating connector)

Mounting type Rear mounting 2-section, lockable

Material

Flammability rating according to UL 94 V0

Sealing material FKM (Form seal)

FKM (O-ring (pin connector pattern))

Additional material specifications PA 6.6 (Fixing sleeve)

Zinc die-cast, nickel-plated (Threaded sleeve)

Color black (Fixing sleeve)

Cable

Standards/specifications M12 connector IEC 61076-2-101

Standards and Regulations

Standard designation M12 connector

Standards/regulations IEC 61076-2-101

Flammability rating...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-BP-F-M12/VAR-2,4/3,2-9TIP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.