

INDUSTRIAL COMPONENT DATA

SACC-CI-M12FS-17P SMD SH T 1411966 PHOENIX CONTACT

Flush-type connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-CI-M12FS-17P SMD SH T



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-CI-M12FS-17P SMD SH T
Catalog number	1411966
Category	Contact insert for circular connectors
Minimum order	60 Pcs
Document ID	EO-E85B371A3F
Generated	2026-08-05

Product Overview

Flush-type connector

Plug-in Mounting Connector, 17-Pole, Connecting Female, Straight, M12, A-Coded, Printed Circuit Board Mounting, SMD, RoHS II Alternative Product Without Exception 6c (Pb< 0.1%) 1238939

Contact carrier, 17-position, Socket, straight, M12, coding: A, PCB mounting, SMD reflow, Alternative product in accordance with RoHS II without Exemption 6c (Pb

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Technical dataNotesNotes on operation The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.

Product propertiesProduct type Contact insert

Application Signal

Number of positions 17

Seal present yes

Shielded yes

Coding A

Thread type M12

Data management status
Article revision 01
Insulation characteristics
Overvoltage category III
Degree of pollution 3
Electrical propertiesRated surge voltage 0.8 kV
Contact resistance $\leq 3 \text{ m}\Omega$
Insulation resistance $\geq 100 \text{ M}\Omega$
Nominal voltage UN 30 V
Nominal current IN 1.5 A
Connection dataConnection method SMD reflow
Material specificationsFlammability rating according to UL 94 V0
Contact material CuZn
Contact surface material Au
Contact carrier material PA
ConnectorConnection 1
Head design Socket
Head cable outlet straight
Head thread type M12
Coding A
Mechanical propertiesMechanical data
Insertion/withdrawal cycles > 100
Environmental and real-life conditionsAmbient conditions
Degree of protection (when plugged in) IP67 (correctly plugged in and locked)
Degree of protection IP67 (correctly plugged in and locked)
IP67, when plugged in
Ambient temperature (operation) $-55 \text{ }^{\circ}\text{C} \dots 105 \text{ }^{\circ}\text{C}$ (Plug / socket)
 $-55 \text{ }^{\circ}\text{C} \dots 105 \text{ }^{\circ}\text{C}$ (without mechanical actuation)
Standards and regula...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-CI-M12FS-17P SMD SH T with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.