

INDUSTRIAL COMPONENT DATA

SACC-CI-M12FS-4P SMD T 1411907 PHOENIX CONTACT

Flush-type connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-CI-M12FS-4P SMD T



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-CI-M12FS-4P SMD T
Catalog number	1411907
Category	Contact insert for circular connectors
Minimum order	60 Pcs
Document ID	EO-2586C63589
Generated	2026-08-05

Product Overview

Flush-type connector

Plug-in Mounting Connector, 4-Pole, Connecting Female, Straight, M12, Coding: A, Printed Circuit Board Mounting, SMD, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) Item code: 1238915

Contact carrier, 4-position, Socket, straight, M12, coding: A, PCB mounting, SMD reflow, Alternative product in accordance with RoHS II without Exemption 6c (Pb)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Technical dataNotesNotes on operation The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.

Product propertiesProduct type Contact insert

Application Signal

Number of positions 4

Seal present no

Shielded no

Coding A

Thread type M12

Data management status

Article revision 02

Insulation characteristics

Overvoltage category II

Degree of pollution 3

Electrical propertiesRated surge voltage 2.5 kV

Contact resistance $\leq 3 \text{ m}\Omega$

Insulation resistance $\geq 100 \text{ M}\Omega$

Nominal voltage UN 250 V

Nominal current IN 4 A

Connection dataConnection method SMD reflow

Material specificationsFlammability rating according to UL 94 V0

Contact material CuZn

Contact surface material Au

Contact carrier material PA

ConnectorConnection 1

Head design Socket

Head cable outlet straight

Head thread type M12

Coding A

Mechanical propertiesMechanical data

Insertion/withdrawal cycles > 100

Environmental and real-life conditionsAmbient conditions

Degree of protection (when plugged in) IP67 (correctly plugged in and locked)

Degree of protection IP67 (correctly plugged in and locked)

IP67, when plugged in

Ambient temperature (operation) $-55 \text{ }^{\circ}\text{C} \dots 105 \text{ }^{\circ}\text{C}$ (Plug / socket)

$-55 \text{ }^{\circ}\text{C} \dots 105 \text{ }^{\circ}\text{C}$ (without mechanical actuation)

Standards and regulations...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-CI-M12FS-4P SMD T with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.