

INDUSTRIAL COMPONENT DATA

SACC-CI-M12FSD-4CON-L180 THR 1414071 PHOENIX CONTACT Bus system flat-type plug

SACC-CI-M12FSD-4CON-L180 THR ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-CI-M12FSD-4CON-L180 THR



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-CI-M12FSD-4CON-L180 THR
Catalog number	1414071
Category	Contact insert for circular connectors
Minimum order	60 Pcs
Document ID	EO-27D75C65BE
Generated	2026-08-06

Product Overview

Bus system flat-type plug - SACC-CI-M12FSD-4CON-L180 THR - 1414071

Plug-in Mounting Connector, 4-Pole, Connecting Female, Straight, Encoding: D, Printed Circuit Board Mounting, Solder Connection THR, RoHS II Alternative Product Without Exception 6c (Pb< 0.1%) Item Code: 1239062

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Bus system flush-type socket, Ethernet, 4-pos., D-coded, with straight THR solder connection, only contact insert

Key Commercial Data

Orderkey 1414071

Packing unit 1

GTIN 4055626063898

Custom tariff number 85389099

Ambient conditions

Degree of protection IP67

General

Note The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap >

IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.

Rated current at 40°C 4 A

Rated voltage 250 V

Rated surge voltage 2.5 kV

Number of positions 4

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding D - data

Standards/regulations M12 connector IEC 61076-2-101

Status display No

Overvoltage category II

Degree of pollution 3

Connection method THR solder connection

Insertion/withdrawal cycles > 100

Torque 3 Nm ... 4 Nm (Installation-side)

Mounting type PCB mounting

Type of packaging Tray

Material

Flammability rating according to UL 94 V0

Contact material CuZn

Contact surface material Au

Contact carrier material PA6T

Sealing material FKM

Cable

Standards/specifications M12 connector IEC 61076-2-101

Standards and Regulations

Standard designation M12 connector

Standards/regulations IEC 61076-2-101

Flammability rating according to UL 94 V0

Environmental Product Compliance

REACH SVHC

Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-CI-M12FSD-4CON-L180 THR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.