

INDUSTRIAL COMPONENT DATA

SACC-CI-M12FSS-4CON-L180 THR PE SP 1421312 PHOENIX CONTACT Sample set SACC-CI-M12FSS-4CON-L180 THR PE SP 142..

Brand: PHOENIX CONTACT | Manufacturer Part Number: 1421312



Manufacturer	PHOENIX CONTACT
MPN / Reference	1421312
Catalog number	SACC-CI-M12FSS-4CON-L180 THR PE SP
Category	Contact insert for circular connectors
Minimum order	1 Pcs
Document ID	EO-5ED157268F
Generated	2026-08-05

Product Overview

Sample set - SACC-CI-M12FSS-4CON-L180 THR PE SP - 1421312

Sample Set, Universal, 4-Pole, Female Connection, Straight, S - Power, Printed Circuit Board Mounting, THR Welding Connection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Sample set, Universal, 4-position, Socket, straight, S power, PCB mounting, THR solder connection

Key Commercial Data

Orderkey 1421312

Packing unit 1

GTIN 4055626257792

Custom tariff number 85389099

Environmental Product Compliance

REACH SVHC

Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCI@ss

eCI@ss 6.0 27279200

eCI@ss 7.0 27440103

eCI@ss 8.0 27440103

eCI@ss 9.0 27440102

ETIM

ETIM 5.0 EC002061

ETIM 6.0 EC002061

UNSPSC

UNSPSC 13.2 39121413

ETIM for 1421312 Connectors (EC002635)

Feature Name

Feature Value

Contact type (EF001587)

Other

Number of data contacts (EF012232)

0

Number of power contacts (EF012216)

0

Number of control contacts (EF012217)

4

Type of housing (EF006980)

Straight

Rated current I_n (EF008250)

12 A

Ambient temperature (EF002386)

-25 °C

Rated voltage (EF000228)

630 V

Over voltage category (EF006785)

III

Pollution degree (EF006786)

3

Material of contact surface (EF004020)

Gold

Housing material (EF001596)

Plastic

Type of locking (EF000208)

Other

Inflammability class of insulation material according to UL94 (EF002521)

V0

With protective conductor (EF007468)

No

Degree of protection (IP), mounted (EF007466)

IP67

Min. number of insertion cycles (EF012212)

100

Screened (EF000881)

No

With status indication (EF001602)

No

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / 1421312 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.