

INDUSTRIAL COMPONENT DATA

SACC-CI-M12FSX-8P SMD SH T 1411964 PHOENIX CONTACT

Flush-type connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-CI-M12FSX-8P SMD SH T



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-CI-M12FSX-8P SMD SH T
Catalog number	1411964
Category	Contact insert for circular connectors
Minimum order	60 Pcs
Document ID	EO-B0DD15ADA8
Generated	2026-08-05

Product Overview

Flush-type connector

Plug-in Mounting Connector, Ethernet, 8-Pole, Female Connection, Straight, M12, Encoding: X, Printed Circuit Board Mounting, SMD, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) Item code: 1238937

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Field Device Connectors (FDC)**

Additional Product Information

Key Commercial Data

Orderkey 1411964

Packing unit 60 pc

Minimum order quantity 60 pc

GTIN 4046356991612

Weight per Piece (excluding packing) 4.500 g

Custom tariff number 85366990

Country of origin DE (Germany)

Ambient conditions

Ambient temperature (operation) -25 °C ... 105 °C (Plug / socket)

-55 °C ... 105 °C (without mechanical actuation)

Degree of protection IP67 (correctly plugged in and locked)

General

Note The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.

Rated current at 40°C 0.5 A (Data)

Rated voltage 50 V AC

60 V DC

Rated surge voltage 1.5 kV

Number of positions 8

Insulation resistance > 100 MΩ

Coding X - data

Standards/regulations M12 connector IEC 61076-2-109 In line with

Signal type/category Ethernet

Overvoltage category III

Degree of pollution 3

Connection method SMD

Insertion/withdrawal cycles > 100

Mounting type PCB mounting

Type of packaging Tray

Delivery state with assembly pad

Material

Flammability rating according to UL 94 V0

Contact material CuZn

Contact surface material Au

Contact carrier material PA

Additional material specifications Zinc die-cast, nickel-plated (Shield crossover)

Cable

Standards/specifications M12 connector IEC 61076-2-109 In line with

Transmission ch...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-CI-M12FSX-8P SMD SH T with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.