

INDUSTRIAL COMPONENT DATA

SACC-CI-M12MSS-4CON-L180THR PE SP 1420412 PHOENIX CONTACT Sample set SACC-CI-M12MSS-4CON-L180THR PE SP 14204..

Brand: PHOENIX CONTACT | Manufacturer Part Number: 1420412



Manufacturer	PHOENIX CONTACT
MPN / Reference	1420412
Catalog number	SACC-CI-M12MSS-4CON-L180THR PE SP
Category	Contact insert for circular connectors
Minimum order	5 Pcs
Document ID	EO-CF97C5ED4A
Generated	2026-08-06

Product Overview

Sample set - SACC-CI-M12MSS-4CON-L180THR PE SP - 1420412

Sample set, Universal, 4-pole, Male connector, straight, S - Power, Printed circuit board mounting, THR welding connection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Sample set, Universal, 4-position, Plug, straight, S power, PCB mounting, THR solder connection

Key Commercial Data

Orderkey 1420412

Packing unit 1

GTIN 4055626224282

Custom tariff number 85366990

Environmental Product Compliance

REACH SVHC

Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCI@ss
eCI@ss 6.0 27279200
eCI@ss 7.0 27440103
eCI@ss 8.0 27440103
eCI@ss 9.0 27440102
ETIM
ETIM 5.0 EC002062
ETIM 6.0 EC002062
UNSPSC
UNSPSC 13.2 39121413
ETIM for 1420412 Connectors (EC002635)
Feature Name
Feature Value
Contact type (EF001587)
Other
Number of data contacts (EF012232)
0
Number of power contacts (EF012216)
0
Number of control contacts (EF012217)
4
Type of housing (EF006980)
Straight
Rated current I_n (EF008250)
12 A
Ambient temperature (EF002386)
-25 °C
Rated voltage (EF000228)
630 V
Over voltage category (EF006785)
III
Pollution degree (EF006786)
3
Material of contact surface (EF004020)
Gold
Housing material (EF001596)
Plastic
Type of locking (EF000208)
Other
Inflammability class of insulation material according to UL94 (EF002521)
V0
With protective conductor (EF007468)
No
Degree of protection (IP), mounted (EF007466)
IP67
Min. number of insertion cycles (EF012212)
100

Screened (EF000881)

No

With status indication (EF001602)

No

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / 1420412 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.