

**INDUSTRIAL COMPONENT DATA**

# SACC-CIP-M8FSB-5P SMD R32 1412252 PHOENIX CONTACT

## Flush-type connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-CIP-M8FSB-5P SMD R32



|                 |                                        |
|-----------------|----------------------------------------|
| Manufacturer    | PHOENIX CONTACT                        |
| MPN / Reference | SACC-CIP-M8FSB-5P SMD R32              |
| Catalog number  | 1412252                                |
| Category        | Contact insert for circular connectors |
| Minimum order   | 120 Pcs                                |
| Document ID     | EO-15BC437642                          |
| Generated       | 2026-08-04                             |

### Product Overview

Flush-type connector

Plug-in connector mounting incorp., Universal, 5-pole, Female connection, straight, M8, B-coded, Mounted on printed circuit boards, SMD

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; Field Device Connectors (FDC)

### Additional Product Information

Key Commercial Data

Orderkey 1412252

Packing unit 100 pc

Minimum order quantity 100 pc

Note Made to Order (non-returnable)

GTIN 4046356988933

Weight per Piece (excluding packing) 111.110 g

Custom tariff number 85366990

Country of origin DE (Germany)

Ambient conditions

Ambient temperature (operation) -25 °C ... 105 °C (Plug / socket)

-40 °C ... 105 °C (without mechanical actuation)

Degree of protection IP67 (correctly plugged in and locked)

## General

Note The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.

Rated current at 40°C 3 A

Rated voltage 30 V

Number of positions 5

Insulation resistance  $\leq 100 \text{ M}\Omega$

Coding B - standard

Standards/regulations M8 connector IEC 61076-2-104

Signal type/category Universal

Overvoltage category II

Connection method SMD

Mounting type PCB mounting

Type of packaging Belt

Material

Flammability rating according to UL 94 V0

Contact material CuZn

Contact surface material Au

Contact carrier material PA

Sealing material FKM

Cable

Standards/specifications M8 connector IEC 61076-2-104

Standards and Regulations

Standard designation M8 connector

Standards/regulations IEC 61076-2-104

Flammability rating according to UL 94 V0

Environmental Product Compliance

REACH SVHC Lead 7439-92-...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-CIP-M8FSB-5P SMD R32 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

## GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.