

INDUSTRIAL COMPONENT DATA

SACC-DSI-FS-12CON-PG9/1,2 SCO 1078715 PHOENIX

CONTACT Flush-type connector

SACC-DSI-FS-12CON-PG9/1,2 SCO 107..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-DSI-FS-12CON-PG9/1,2 SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-DSI-FS-12CON-PG9/1,2 SCO
Catalog number	1078715
Category	Circular connector, mounting (with cable)
Minimum order	50 Pcs
Document ID	EO-7635172E4B
Generated	2026-08-05

Product Overview

Flush-type connector - SACC-DSI-FS-12CON-PG9/1,2 SCO - 1078715

Sensor/actuator mounting female, 12-pole, SPEEDCON M12, rear wall mount/Pg9 threaded screw mount, with 0.5 m halogen-free TPE braided yarn, 12 x 0.14 mm²

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Sensor/actuator flush-type socket, 12-pos., M12 SPEEDCON, rear/screw mounting with Pg9 thread, with 0.5 m halogen-free TPE litz wire, 12 x 0.14 mm²

Key Commercial Data

Orderkey 1078715

Packing unit 1

GTIN 4055626794334

Custom tariff number 85444290

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCI@ss

eCI@ss 8.0 27440103

eCI@ss 9.0 27440102

ETIM

ETIM 5.0 EC002061

ETIM for 1078715 Connectors (EC003570)

Feature Name

Feature Value

Cable length (EF000536)

1.2 mm

Type of plug-in contact, outer side (EF005528)

None

Mounting method (EF000003)

Back wall mounting

Housing material (EF001596)

Other

Material core insulation (EF000061)

Other

Material of contact surface (EF004020)

Other

Inflammability class of insulation material according to UL94 (EF002521)

V0

Ambient temperature (EF002386)

85 °C

Operating temperature (EF002393)

-25 °C

Rated voltage (EF000228)

30 V

With shield connection (EF002535)

No

Screw-in thread (EF012303)

M12

Core cross section (EF000018)

0.14 mm²

Min. number of insertion cycles (EF012212)

100

Degree of protection (IP), mounted (EF007466)

Other

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-DSI-FS-12CON-PG9/1,2 SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.