

INDUSTRIAL COMPONENT DATA

SACC-DSI-FS-5CON-PG9/2,0PE SCO 1401201 PHOENIX CONTACT Panel feed-through

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-DSI-FS-5CON-PG9/2,0PE SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-DSI-FS-5CON-PG9/2,0PE SCO
Catalog number	1401201
Category	Sensor-actuator connector chassis
Minimum order	50 Pcs
Document ID	EO-F8E07197D5
Generated	2026-08-05

Product Overview

Panel feed-through

Female mounting inc. for sensors/actuators, 5 poles, SPEEDCON M12, A-coded, rear wall mounting/bolted mounting, with Pg9 thread, with 2 m TPE braided wire, 5 x 0.34 mm², green/yellow conductor over PIN5

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1401201

Packing unit 1 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4046356536264

Weight per Piece (excluding packing) 59.200 g

Custom tariff number 85444290

Country of origin DE (Germany)

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.027250313eCl@ss 4.127250313eCl@ss 5.027143423eCl@ss 5.127143400eCl@ss 6.027279200eCl@ss
7.027440103eCl@ss 8.027440103eCl@ss 9.027440102

ETIM 3.0EC002061ETIM 4.0EC002061ETIM 5.0EC002061ETIM 6.0EC002061

UNSPSC 6.0131261501UNSPSC 7.090131261501UNSPSC 1131261501UNSPSC 12.0131261501UNSPSC
13.239121413

ETIM for 1401201 Connectors (EC003570)

Feature Name**Feature Value**

Cable length (EF000536)

2 mm

Mounting method (EF000003)

Back wall mounting

Housing material (EF001596)

Other

Material core insulation (EF000061)

Other

Material of contact surface (EF004020)

Other

Inflammability class of insulation material according to UL94 (EF002521)

V0

Ambient temperature (EF002386)

85 °C

Operating temperature (EF002393)

-25 °C

Rated voltage (EF000228)

60 V

With shield connection (EF002535)

No

Screw-in thread (EF012303)

M12

Core cross section (EF000018)

0.34 mm²

Degree of protection (IP), mounted (EF007466)

Other

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-DSI-FS-5CON-PG9/2,0PE SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.