

INDUSTRIAL COMPONENT DATA

SACC-DSI-FS-8CON-PG 9/0,3 SCO 1414569 PHOENIX CONTACT Connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-DSI-FS-8CON-PG 9/0,3 SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-DSI-FS-8CON-PG 9/0,3 SCO
Catalog number	1414569
Category	Circular connector, mounting (with cable)
Minimum order	50 Pcs
Document ID	EO-43B7EB9C8F
Generated	2026-08-01

Product Overview

Connector

Conect. plug. to be apar. wall poster., Universal, 8-pole, Connecting female, straight, M12-SPEEDCON, coding: A, free cable end, Rear wall mounting, Pg9, Single stranded wires, cable length: 0.3 m, 0.25 mm², TPE braided wire, Alternative product according to RoHS II without exception 6c (Pb <. 0.1%) art.code: 1239073

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1414569

Packing unit 1

GTIN 4055626030098

Custom tariff number 85444290

Environmental Product Compliance

Classifications

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Back to topClassifications

eCI@ss

eCI@ss 10.0.1 27440102

eCI@ss 5.1 27143423

eCI@ss 6.0 27143423

eCI@ss 8.0 27440103

eCI@ss 9.0 27440102

Back to topETIM

ETIM 5.0 EC002061

ETIM 6.0 EC002061

Back to topUNSPSC

UNSPSC 13.2 39121413

UNSPSC 18.0 39121413

UNSPSC 19.0 39121413

UNSPSC 20.0 39121413

UNSPSC 21.0 39121413

Back to top

ETIM for 1414569 Connectors (EC003570)

Feature Name

Feature Value

Cable length (EF000536)

0.3 mm

Type of plug-in contact, outer side (EF005528)

None

Mounting method (EF000003)

Back wall mounting

Housing material (EF001596)

Other

Material core insulation (EF000061)

Other

Material of contact surface (EF004020)

Other

Inflammability class of insulation material according to UL94 (EF002521)

V0

Ambient temperature (EF002386)

85 °C

Operating temperature (EF002393)

-25 °C

Rated voltage (EF000228)

30 V

With shield connection (EF002535)

No

Screw-in thread (EF012303)

M12

Core cross section (EF000018)

0.25 mm²

Min. number of insertion cycles (EF012212)

100

Degree of protection (IP), mounted (EF007466)

Other

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-DSI-FS-8CON-PG 9/0,3 SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.