

INDUSTRIAL COMPONENT DATA

SACC-DSI-M12FS-12CON-M16/2,0 1458790 PHOENIX CONTACT Flush-type connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-DSI-M12FS-12CON-M16/2,0



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-DSI-M12FS-12CON-M16/2,0
Catalog number	1458790
Category	Circular connector, mounting (with cable)
Minimum order	1 Pcs
Document ID	EO-E718E399AF
Generated	2026-08-06

Product Overview

Flush-type connector

Built-in sensor/actuator mounting female, 12-pole, SPEEDCON M12, rear wall mount/screwed mounting with M16 thread, with 2.0 m halogen-free TPE braided wire, 12 x 0.14 mm²

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1458790

Packing unit 1 pc

Minimum order quantity 100 pc

Note Made to Order (non-returnable)

GTIN 4046356645041

Weight per Piece (excluding packing) 71.600 g

Custom tariff number 85444290

Country of origin DE (Germany)

Dimensions

Length of cable 2 m

Ambient conditions

Degree of protection IP67

General

Rated current at 40°C 1.5 A

Rated voltage 30 V

Rated surge voltage 0.8 kV

Number of positions 12

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding A - standard

Standards/regulations M12 connector IEC 61076-2-101

Status display No

Overvoltage category II

Degree of pollution 3

Connection method Individual wires

Mounting type Rear mounting M16 x 1.5 With flat nut

Material

Flammability rating according to UL 94 V0

Contact material CuZn

Contact surface material Au

Contact carrier material PA 6.6

Material, knurls Zinc die-cast, nickel-plated

Sealing material NBR

Cable

Cable type TPE litz wire

AWG signal line 26

Wire colors Color-coded DIN 47100

Conductor material Tin-plated Cu litz wires

Standards/specifications M12 connector IEC 61076-2-101

Standards and Regulations

Standard designation M12 connector

Standards/regulations IEC 61076-2-101

Flammability rating according to UL 94 V0

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 4.027250313eCl@ss 4.127250313eCl@ss 5.027250313eCl@ss 5.127...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-DSI-M12FS-12CON-M16/2,0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.