


INDUSTRIAL COMPONENT DATA

SACC-DSI-M12FS-4P-M16/1,5 1414072 PHOENIX CONTACT

Flush-type connector SACC-DSI-M12FS-4P-M16/1,5 1414072

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-DSI-M12FS-4P-M16/1,5



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-DSI-M12FS-4P-M16/1,5
Catalog number	1414072
Category	Circular connector, mounting (with cable)
Minimum order	50 Pcs
Document ID	EO-A5F7653FDD
Generated	2026-08-05

Product Overview

Flush-type connector - SACC-DSI-M12FS-4P-M16/1,5 - 1414072

Built-in mounting female for sensors/actuators, 4 poles, SPEEDCON M12, rear wall mounting/screw-on mounting with M16 thread, with 1.5 m TPE braided wire, 4 x 0.34 mm²

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Sensor/actuator flush-type socket, 4-pos., M12 SPEEDCON, rear/screw mounting with M16 thread, with 0.5 m TPE litz wire, 4 x 0.34 mm²

Key Commercial Data

Orderkey 1414072

Packing unit 1

GTIN 4055626013589

Custom tariff number 85444290

Environmental Product Compliance

REACH SVHC

Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCI@ss

eCI@ss 5.1 27143423

eCI@ss 6.0 27279200

eCI@ss 7.0 27440103

eCI@ss 8.0 27440103

eCI@ss 9.0 27440102

ETIM

ETIM 5.0 EC002061

ETIM 6.0 EC002061

UNSPSC

UNSPSC 13.2 39121413

ETIM for 1414072 Connectors (EC003570)

Feature Name

Feature Value

Cable length (EF000536)

1.5 mm

Type of plug-in contact, outer side (EF005528)

None

Mounting method (EF000003)

Back wall mounting

Housing material (EF001596)

Other

Material core insulation (EF000061)

Other

Material of contact surface (EF004020)

Other

Inflammability class of insulation material according to UL94 (EF002521)

V0

Ambient temperature (EF002386)

85 °C

Operating temperature (EF002393)

-25 °C

Rated voltage (EF000228)

250 V

With shield connection (EF002535)

No

Screw-in thread (EF012303)

M12

Core cross section (EF000018)

0.34 mm²

Min. number of insertion cycles (EF012212)

100

Degree of protection (IP), mounted (EF007466)

Other

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-DSI-M12FS-4P-M16/1,5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.