

INDUSTRIAL COMPONENT DATA

SACC-DSI-M12FS-5CON-PG9-L180 1409463 PHOENIX CONTACT

Sensor/actuator flush-type male connector, 5-pos., M12 ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-DSI-M12FS-5CON-PG9-L180



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-DSI-M12FS-5CON-PG9-L180
Catalog number	1409463
Category	Circular connector, mounting (PCB)
Minimum order	200 Pcs
Document ID	EO-A2A55A86E9
Generated	2026-08-04

Product Overview

Sensor/actuator flush-type male connector, 5-pos., M12 standard thread, A-coded, rear/screw mounting with Pg9 thread, with straight solder connection

Conect. plug. to be apar. wall poster., 5-pole, Connecting female, M12, coding: A, Rear mounting, Wave welding, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) art.code: 1238818

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Field Device Connectors (FDC)**

Additional Product Information

Key Commercial Data

Orderkey 1409463

Packing unit 1 pc

Minimum order quantity 200 pc

GTIN 4046356893558

Weight per Piece (excluding packing) 14.000 g

Custom tariff number 85366990

Country of origin DE (Germany)

Drawings

Material

[Standards and Regulations](#)[Classifications](#)[General](#)[Cable](#)[Environmental Product Compliance](#)[Drawings](#)[Drilling diagram](#)[Dimensional drawing](#)[M12 flush-type connector](#)[Dimensional drawing](#)[Housing cutout for Pg9 fastening thread, mounting panel with feed-through hole \(alternatively with area as anti-rotation protection for panel thicknesses > 2 mm up to max. 4.5 mm\)](#)[Dimensional drawing](#)[M12 front view](#)[Schematic diagram](#)[Pin assignment M12 socket, 5-pos., A-coded, socket side view](#)[Back to top](#)[General](#)

Note The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.

[Rated current at 40°C 4 A](#)[Rated voltage 60 V](#)[Number of positions 5](#)[Standards/regulations M12 connector IEC 61076-2-101](#)[Overvoltage category II](#)[Degree of pollution 3](#)[Back to top](#)[Material](#)[Flammability rating according to UL 94 V0](#)[Back to top](#)[Cable](#)[Standards/specifications M12 connector IEC 61076-2-101](#)[Back to top](#)[Standards and Regulations](#)[Standards/specifications M12 connector IEC 61076-2-101](#)[Flammability rating according to UL 94 V0....](#)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-DSI-M12FS-5CON-PG9-L180 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.